

Title (en)

PROCESS FOR MANUFACTURING BEAMS WITH SINGLE OR MULTIPLE CASTELLATION, AND CASTELLATED BEAMS THUS OBTAINED

Publication

EP 0333827 B1 19920102 (DE)

Application

EP 88908742 A 19881006

Priority

HU 458487 A 19871012

Abstract (en)

[origin: WO8903464A1] The beam is subdivided longitudinally into sections in function of the anticipated static load or, when the whole beam is to be subjected to a single characteristic load, it is considered to constitute a single section; the web of the section(s) is then cut into two halves along a cutting line (3) composed of straight lines and curves of variable periodicity in a rotationally symmetric manner in relation to the point (o) located on a median line (k) perpendicular to the length of the sections. The dimensions of the castellations so obtained are thus adapted to the load. One of the halves (2) so obtained is rotated through 180 DEG about the median line, the two halves of the beam are jointed together to form a web, and, in the case of several sections, the castellated sections so obtained are joined together.

IPC 1-7

E04C 3/04

IPC 8 full level

E04C 3/04 (2006.01); **E04C 3/08** (2006.01); **E04C 3/40** (2006.01)

CPC (source: EP)

E04C 3/086 (2013.01); **E04C 3/40** (2013.01); E04C 2003/0413 (2013.01); **E04C 2003/0434** (2013.01); **E04C 2003/0452** (2013.01)

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

WO 8903464 A1 19890420; AT E71168 T1 19920115; AU 2533588 A 19890502; DE 3867462 D1 19920213; EP 0333827 A1 19890927; EP 0333827 B1 19920102; HU 206400 B 19921028; HU T51698 A 19900528

DOCDB simple family (application)

HU 8800065 W 19881006; AT 88908742 T 19881006; AU 2533588 A 19881006; DE 3867462 T 19881006; EP 88908742 A 19881006; HU 458487 A 19871012