

Title (en)
SEALING ARRANGEMENT FOR DOORS

Publication
EP 0334307 B1 19931013 (DE)

Application
EP 89105081 A 19890322

Priority
DE 3809669 A 19880323

Abstract (en)
[origin: EP0334307A2] The sealing arrangement is used for closed doors to seal the gap between the floor and the lower edge of the door. A switch for an electromagnet (55) is assigned to a sealing body (23) as a triggering element for moving said body into the sealing position. The switch is connected to the sealing body (23) via a lifting device (29, 30) having an armature (44). By means of the switch, the electromagnet (55) is excited upon closure of the door, then draws the armature (44) and moves the sealing body (23) out of a support (1) via the lifting device (29, 30) and into the sealing position. <IMAGE>

IPC 1-7
E06B 7/215

IPC 8 full level
E06B 7/20 (2006.01); **E06B 7/215** (2006.01)

CPC (source: EP)
E06B 7/20 (2013.01); **E06B 7/215** (2013.01)

Cited by
DE3935790A1; US5253453A; EP0609755A1; DE20005376U1; US5339488A; EP0489537A1; EP1944457A3; EP2682556A1; EP0424708B1

Designated contracting state (EPC)
AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)
EP 0334307 A2 19890927; EP 0334307 A3 19900606; EP 0334307 B1 19931013; AT E95881 T1 19931015; DE 3809669 A1 19891012; DE 3809669 C2 19961024; DE 58905866 D1 19931118

DOCDB simple family (application)
EP 89105081 A 19890322; AT 89105081 T 19890322; DE 3809669 A 19880323; DE 58905866 T 19890322