

Title (en)
DEVICE FOR THE RELATIVE ANGULAR DISPLACEMENT BETWEEN TWO GEARED SHAFTS

Publication
EP 0335083 B1 19910911 (DE)

Application
EP 89102105 A 19890208

Priority
DE 3810804 A 19880330

Abstract (en)
[origin: EP0335083A1] An adjusting piston (6), which can move axially between a driven sprocket wheel support (3) and a flanged shaft (9) connected to a cam shaft (11), divides the cavity formed by the sprocket wheel support (3) and the flanged shaft (9) into two operating chambers (15, 16). The adjusting piston (6) is connected both to the sprocket wheel support (3) and to the flanged shaft (9) in a positively locking manner via helical gear wheels (2, 4, 7, 8). Depending on the position of a control piston (17) arranged in the hollow flanged shaft (9), oil under pressure is supplied from the motor oil circuit into the one operating chamber or the other (15, 16) and displaces the adjusting piston (6) in the axial direction. This longitudinal movement of the adjusting piston causes a relative rotation of the cam shaft (11) with respect to the driven sprocket wheel support (3), via the two helical gear wheels (2, 4, 7, 8). The movement takes place entirely hydraulically in both directions, without any form of auxiliary force.
<IMAGE>

IPC 1-7
F01L 1/34

IPC 8 full level
F01L 1/34 (2006.01); **F01L 1/344** (2006.01)

CPC (source: EP US)
F01L 1/34406 (2013.01 - EP US)

Cited by
US4976229A; DE4027631C1; US5305717A; FR2643941A1; EP0469334A1; US5170756A; DE4024057C1; EP0469332A1; US5138985A; US5566651A; DE4218082C2; DE4218082C5; US8733306B2; US11028738B2; WO2018019633A1; WO2011117019A1

Designated contracting state (EPC)
DE ES FR GB IT SE

DOCDB simple family (publication)
EP 0335083 A1 19891004; EP 0335083 B1 19910911; DE 3810804 A1 19891019; DE 3810804 C2 19900913; DE 58900270 D1 19911017; ES 2026703 T3 19920501; JP H01300006 A 19891204; JP H0686807 B2 19941102; US 4895113 A 19900123

DOCDB simple family (application)
EP 89102105 A 19890208; DE 3810804 A 19880330; DE 58900270 T 19890208; ES 89102105 T 19890208; JP 7526789 A 19890329; US 33045989 A 19890330