

Title (en)
METHOD FOR GRINDING A POLYGON CONE ON AN NC GRINDING MACHINE

Publication
EP 0335255 B1 19930915 (DE)

Application
EP 89105211 A 19890323

Priority
DE 3810422 A 19880326

Abstract (en)
[origin: EP0335255A2] The method serves to grind a cone (14a) whose radial cross-sectional area has the configuration of an n-cornered polygon profile with predetermined eccentricity and a predetermined arithmetic mean D_m of the diameters of the circumscribed circle and the inscribed circle of the polygon profile. A grinding wheel (40a) which is rotatable about a first axis (42a) acts along a common generating line (41a) on a [lacuna] about a second axis (43a) [lacuna] intersect at an acute angle (λ). The grinding wheel (40a) performs an oscillating movement during which the generating line (41a), with the n-fold frequency of the rotary movement of the workpiece blank (46a) and with an amplitude corresponding to twice the eccentricity, is displaced in parallel in the plane defined by the axes (42a, 43a). So that a polygon cone (14a) can be ground with a grinding wheel which can be produced industrially and has a straight generating line (41a), the radial cross-sectional areas of which polygon cone (14a) are brought as close as possible to the ideal constant-diameter profile (from the criteria of the science of materials) according to DIN 32 711, the amplitude is set with an eccentricity e' which obeys the relationship $e' = \frac{D_m}{2 \cdot \sin(\lambda)}$ where D_m is the arithmetic mean of the diameters of the polygon profile at the pointed end of the cone (14a), and λ is a predetermined angle of preferably 14 DEG .

IPC 1-7
B24B 19/08

IPC 8 full level
B24B 19/08 (2006.01)

CPC (source: EP)
B24B 19/08 (2013.01)

Cited by
CN109702564A; CN113523713A; CN1097160C; US6293100B1; WO9902854A1

Designated contracting state (EPC)
AT CH DE FR GB IT LI SE

DOCDB simple family (publication)
EP 0335255 A2 19891004; EP 0335255 A3 19900822; EP 0335255 B1 19930915; AT E94446 T1 19931015; DE 58905584 D1 19931021

DOCDB simple family (application)
EP 89105211 A 19890323; AT 89105211 T 19890323; DE 58905584 T 19890323