

Title (en)

JIG SAW HAVING AN ORIENTABLE SAW BLADE

Publication

**EP 0335837 A3 19910116 (FR)**

Application

**EP 89810228 A 19890322**

Priority

CH 71288 A 19880330

Abstract (en)

[origin: EP0335837A2] The blade of this saw, which can move about its longitudinal axis, can be oriented during the cutting by the handle or by a wheel. If it is directed by the wheel, the handle then directs the frame. If the handle directs the blade, the frame is free in its orientation. In order to prevent the blade from twisting, its tenons must be synchronised by a member which runs along the frame and which consists of a belt device, rods and gears or of teleflex cables. In order to give the inoperative elements play with respect to twisting, the movements of the control element are initially transmitted to the centre of the tenon-synchronisation device which re-transmits them symmetrically to the tenons. <IMAGE>

IPC 1-7

**B23D 49/00; B27B 19/14**

IPC 8 full level

**B27B 19/14** (2006.01)

CPC (source: EP)

**B27B 19/14** (2013.01)

Designated contracting state (EPC)

AT BE DE FR GB

DOCDB simple family (publication)

**EP 0335837 A2 19891004; EP 0335837 A3 19910116; CH 673246 A5 19900228**

DOCDB simple family (application)

**EP 89810228 A 19890322; CH 71288 A 19880330**