

Title (en)
INSERTION MACHINE

Publication
EP 0336062 B1 19920318 (DE)

Application
EP 89101556 A 19890130

Priority
CH 123688 A 19880331

Abstract (en)
[origin: EP0336062A2] The insertion machine is provided with pockets (3) which are arranged at regular intervals and can be moved along a continuous path (1, 2), along which are successfully arranged a main product insert (4), at least one supplement-inserting station (6) and a removal station (7). Means are also provided to open printed products (31) in the pockets (3), upstream of the supplement-inserting station (6). To make it possible for the machine to be reset rapidly for a new main product irrespective of the size of the machine, such means are arranged to run synchronously with the pockets (3) along a section of the continuous path (1, 2) upstream of each inserting station (6). <IMAGE>

IPC 1-7
B65H 5/30

IPC 8 full level
B65H 29/16 (2006.01); **B65H 5/30** (2006.01); **B65H 39/065** (2006.01)

CPC (source: EP US)
B65H 5/301 (2013.01 - EP US); **B65H 31/3081** (2013.01 - EP US); **B65H 2301/361** (2013.01 - EP US); **B65H 2301/432** (2013.01 - EP US); **B65H 2404/33** (2013.01 - EP US)

Cited by
CH708427A1; EP1310444A1; EP0475192A3; US5251888A; EP0573390A1; US5421568A; US6168152B1; US6311968B1; US9227803B2; US6820870B2

Designated contracting state (EPC)
AT DE FR GB IT

DOCDB simple family (publication)
EP 0336062 A2 19891011; EP 0336062 A3 19900117; EP 0336062 B1 19920318; AT E73730 T1 19920415; CH 674511 A5 19900615; DE 58900970 D1 19920423; JP 2735608 B2 19980402; JP H01303263 A 19891207; US 5050851 A 19910924

DOCDB simple family (application)
EP 89101556 A 19890130; AT 89101556 T 19890130; CH 123688 A 19880331; DE 58900970 T 19890130; JP 7481789 A 19890327; US 31773789 A 19890302