

Title (en)

Rechargeable dispenser with a moving piston.

Title (de)

Beladbarer Spender mit einem verschiebbaren Kolben.

Title (fr)

Distributeur rechargeable comportant un piston translatable.

Publication

EP 0337867 A1 19891018 (FR)

Application

EP 89400977 A 19890410

Priority

FR 8805026 A 19880415

Abstract (en)

[origin: JPH0219290A] PURPOSE: To obtain a dispenser equipped with an interchangeable reservoir by providing the reservoir with a frustoconical surface that comes to be pressed against a corresponding frustoconical surface of a nut or a support or both of them when integrally joining the reservoir to the support and tightening each sector of the nut around a threaded rod. CONSTITUTION: When a support 7 is further pushed forward in the cylindrical portion 1b so as to fit this, thread of a rod 5 pushes to widen two half-nuts separated by a slit 10 because these two half-nuts are not mutually restricted. The rod 5 slides in a nut 9 accompanied by friction until the nut 9 returns to the position where the refraction completely finishes within the support 7. And a plunger 4 pushes a flat portion 12 of the nut 9. It pushes the frustoconical surface 1c when reaching this position, and makes the two half-nuts no longer being capable of spreading apart by locking them. In this manner, the screw of the hole 11 engages again with the screw of the rod 5, which is thus driven so as to perform translation with respect to the reservoir I when the rod 5 starts rotating with mechanism integrated in the support 7, so that the product 3 can be dispensed.

Abstract (fr)

L'invention concerne un distributeur de produit (3) compact contenu dans un réservoir cylindrique (1) ; le produit (3) est éjecté par un piston (4) déplaçable en translation dans le réservoir et monté en bout d'une tige filetée (5), qui coopère avec un écrou (9). La tige (5) est entraînée en rotation pas à pas par un bouton-poussoir (8). Le support (7) du mécanisme et de l'écrou (9) est amovible par rapport au réservoir (1) grâce à un filetage. L'écrou (9) qui coopère avec la tige (5) est fendu selon un plan diamétral pour autoriser le réenfoncement de la tige quand les demi-écrous peuvent s'écartier. Le réservoir comporte une portée tronconique (1c), qui assure le pincement des demi-écrous quand le mécanisme est mis en place à la base du réservoir plein.

IPC 1-7

A45D 40/04

IPC 8 full level

A45D 40/02 (2006.01); **A45D 40/04** (2006.01); **B65D 83/00** (2006.01)

CPC (source: EP KR US)

A45D 40/00 (2013.01 - KR); **A45D 40/04** (2013.01 - EP US)

Citation (search report)

- [A] US 3358699 A 19671219 - GORDON BAU ROBERT
- [A] EP 0015784 A1 19800917 - PILOT PEN CO LTD [JP]
- [AD] FR 2555471 A1 19850531 - PENTEL KK [JP]
- [A] FR 1343108 A 19631115 - BODENSEE DENTAL OHG

Cited by

EP0604793A1; FR2770108A1; FR2770107A1; FR2752697A1; US6071027A; FR2735667A1; FR2964540A1; US10888148B2; WO9809548A1; WO9325113A1; EP3415035B1

Designated contracting state (EPC)

DE ES GB IT

DOCDB simple family (publication)

EP 0337867 A1 19891018; EP 0337867 B1 19931103; DE 68910370 D1 19931209; DE 68910370 T2 19940601; ES 2046499 T3 19940201; FR 2629988 A1 19891020; FR 2629988 B1 19900810; JP 2617788 B2 19970604; JP H0219290 A 19900123; KR 890015700 A 19891125; KR 960015644 B1 19961120; US 4954000 A 19900904

DOCDB simple family (application)

EP 89400977 A 19890410; DE 68910370 T 19890410; ES 89400977 T 19890410; FR 8805026 A 19880415; JP 9327289 A 19890414; KR 890005076 A 19890415; US 33822689 A 19890414