

Title (en)
COLUMN DRYER WITH INVERSED V-SHAPED DEFLECTORS FOR POURABLE MATERIAL

Publication
EP 0339196 A3 19900117 (DE)

Application
EP 89102567 A 19890215

Priority
DE 8805479 U 19880426

Abstract (en)
[origin: EP0339196A2] The discharge device of a column dryer has numerous funnels (15), under which sliders (22) are arranged. Each slider (22) is displaceable between a first operating position (B11), in which one slot edge (17a) of the funnel is opened, and a second operating position (B21), in which the other slot edge (17b) is opened, the operating positions changing periodically. For residual emptying, the slider (22) can be moved into a position (B3) outside the slot (17). <IMAGE>

IPC 1-7
F26B 17/12; F26B 25/00; B65D 90/60

IPC 8 full level
F26B 17/14 (2006.01); **F26B 25/00** (2006.01)

CPC (source: EP)
F26B 17/1416 (2013.01); **F26B 25/002** (2013.01)

Citation (search report)

- [XP] DE 8805479 U1 19880601
- [Y] FR 578235 A 19240920
- [Y] US 2660810 A 19531201 - HESS BRYCE M
- [A] FR 460577 A 19131205 - PELLEGRINO FLII SOC [IT]
- [A] FR 2444907 A1 19800718 - BUEHLER MIAG GMBH [DE]
- [A] GB 1102402 A 19680207 - HANS PETER PEDERSEN
- [A] AU 436777 B2 19730613
- [Y] PATENT ABSTRACTS OF JAPAN, Band 7, Nr. 74 (M-203)[1219], 26. März 1983; & JP-A-58 002 131 (NIPPON KOKAN K.K.) 07-01-1983

Cited by
CN107879130A; US8572863B2

Designated contracting state (EPC)
AT BE CH DE FR GB GR IT LI LU NL

DOCDB simple family (publication)
DE 8805479 U1 19880601; EP 0339196 A2 19891102; EP 0339196 A3 19900117

DOCDB simple family (application)
DE 8805479 U 19880426; EP 89102567 A 19890215