

Title (en)
Sealed, high flux neutron tube.

Title (de)
Abgedichtete Hochfluss-Neutronenröhre.

Title (fr)
Tube neutronique scellé, à haut flux.

Publication
EP 0340832 A1 19891108 (FR)

Application
EP 89201010 A 19890420

Priority
FR 8805510 A 19880426

Abstract (en)

Device comprising a first part and a second part which are separated by the acceleration electrode (13) which forms a shield between the said parts and is integral with the earthed outer surround (15). <??>The said first and second parts of the tube contain respectively the ion source (9), brought to a positive potential of adjustable value, and the target (28), brought to a negative potential of likewise adjustable value, relative to the zero value of earth. <??>Application: neutron radiography. <IMAGE>

IPC 1-7
H05H 5/00

IPC 8 full level
G21G 4/02 (2006.01); **G21K 5/02** (2006.01); **G21K 5/08** (2006.01); **H05H 3/06** (2006.01)

CPC (source: EP US)
H05H 3/06 (2013.01 - EP US)

Citation (search report)

- [X] US 2985760 A 19610523 - GALE ALFRED J
- [A] US 2907884 A 19591006 - GALE ALFRED J
- [A] NL 7707357 A 19790108 - PHILIPS NV
- [A] US 4119858 A 19781010 - CRANBERG LAWRENCE
- [A] FR 2167619 A1 19730824 - PHILIPS NV [NL]
- [A] NUCLEAR INSTRUMENTS AND METHODS, vol. 189, 1981, pages 103-106, North-Holland Publishing Co., Amsterdam, NL; J.K. HIRVONEN et al.: "Production of high-current metal ion beams"
- [AD] PHILIPS TECHNICAL REVIEW, vol. 41, no. 1, 1983/84, pages 24-29, Eindhoven, NL; W. HARTL et al.: "Metal/ceramic X-ray tubes for non-destructive testing"

Cited by
BG65440B1; US6441569B1; US6797701B2; EP2347654A1; EP3488698A1

Designated contracting state (EPC)
DE FR GB

DOCDB simple family (publication)
EP 0340832 A1 19891108; EP 0340832 B1 19931229; DE 68911741 D1 19940210; DE 68911741 T2 19940630; FR 2630576 A1 19891027; FR 2630576 B1 19900817; JP H0213900 A 19900118; US 5053184 A 19911001

DOCDB simple family (application)
EP 89201010 A 19890420; DE 68911741 T 19890420; FR 8805510 A 19880426; JP 10477589 A 19890426; US 34311589 A 19890425