

Title (en)
THERMAL PRINTER

Publication
EP 0340855 A3 19900124 (DE)

Application
EP 89201090 A 19890427

Priority
AT 114788 A 19880503

Abstract (en)
[origin: EP0340855A2] In a thermal printer with a thermal printing head (15) adjustable in the line direction and with a writing strip (6) extending in the line direction, located opposite the thermal printing head and arranged pivotably transversely relative to the line direction, a supporting part (19) of the writing strip, forming an abutment for the thermal printing head, is connected, via at least one strip-shaped hinge part (20) projecting centrally from the supporting part, extending at least partially in the line direction and being intrinsically resilient transversely relative to the line direction, to a batten-like mounting part (21) extending parallel to the supporting part and retained on the printer. <IMAGE>

IPC 1-7
B41J 11/08

IPC 8 full level
B41J 11/02 (2006.01); **B41J 11/08** (2006.01)

CPC (source: EP US)
B41J 11/08 (2013.01 - EP US)

Citation (search report)
• [A] US 4676683 A 19870630 - UCHIKATA YOSHIO [JP], et al
• [A] PATENT ABSTRACTS OF JAPAN vol. 11, no. 258 (M-618)(2705) 21 August 1987, & JP-A-62 64578 (H. FUJINO) 23 März 1987,

Designated contracting state (EPC)
AT DE FR GB IT SE

DOCDB simple family (publication)
EP 0340855 A2 19891108; EP 0340855 A3 19900124; EP 0340855 B1 19930310; AT 390033 B 19900312; AT A114788 A 19890815; AT E86554 T1 19930315; DE 58903693 D1 19930415; JP H0211360 A 19900116; US 4940994 A 19900710

DOCDB simple family (application)
EP 89201090 A 19890427; AT 114788 A 19880503; AT 89201090 T 19890427; DE 58903693 T 19890427; JP 11273989 A 19890501; US 34539389 A 19890501