

Title (en)
BOILER

Publication
EP 0340859 B1 19920923 (EN)

Application
EP 89201098 A 19890427

Priority
NL 8801131 A 19880429

Abstract (en)

[origin: EP0340859A1] Boiler for extraction by combustion from random flammable material of thermal energy with a flow duct comprising an exhaust device connected to an outlet side of the duct, a first cylindrical combustion chamber (4) close to the intake side, a second cylindrical combustion chamber (5) connected to the first combustion chamber via a connecting duct portion whereby the connecting duct portion runs out tangentially into the second combustion chamber, and additional air supply means (11) for supplying additional combustion air into the second combustion chamber. The first and second combustion chambers are arranged coaxially and are separated from one another by a first dividing wall (6) comprising in the upper portion a tangential passage opening (7), a discharge chamber (10) with a discharge on the periphery connects onto the second combustion chamber via a second dividing wall (8) with a central passage opening (9), and the additional air supply means comprise an air supply pipe debouching into the discharge chamber at a distance opposite the central passage opening and having a smaller diameter than the passage opening.

IPC 1-7
F22B 31/00; F23B 1/08; F23B 5/04; F23G 5/16

IPC 8 full level
F22B 31/00 (2006.01); **F23G 5/16** (2006.01); **F23G 7/00** (2006.01)

CPC (source: EP)
F23B 5/04 (2013.01)

Cited by
EP0525711A3; DE4033406A1; EP0482306A3; EP0905442A3

Designated contracting state (EPC)
AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)
EP 0340859 A1 19891108; EP 0340859 B1 19920923; AT E80931 T1 19921015; DE 68902948 D1 19921029; DE 68902948 T2 19930422;
ES 2035524 T3 19930416; GR 3006219 T3 19930621; NL 8801131 A 19891116

DOCDB simple family (application)
EP 89201098 A 19890427; AT 89201098 T 19890427; DE 68902948 T 19890427; ES 89201098 T 19890427; GR 920402555 T 19921112;
NL 8801131 A 19880429