

Title (en)

METHOD FOR SUPPORTING AN ANCHORAGE HEAD OF A TENSIONED INJECTION ANCHOR ON A SUPPORT, AND AN INJECTION ANCHOR FOR APPLYING THIS METHOD

Publication

EP 0341568 A3 19891220 (DE)

Application

EP 89108024 A 19890503

Priority

DE 3816222 A 19880511

Abstract (en)

[origin: EP0341568A2] The method for supporting an anchorage head (10, 10') of a tensioned injection anchor (1) on a support (7) provides for the anchorage head (10, 10'), located at a distance from the support (7), to be supported by a distance element after the re-tensioning of one or more tension members (3). A hard granular or hardenable material is fed as a distance element into the intermediate space between support and anchorage head. <IMAGE>

IPC 1-7

E02D 5/76

IPC 8 full level

E02D 5/76 (2006.01)

CPC (source: EP)

E02D 5/76 (2013.01)

Citation (search report)

- [X] DE 928518 C 19550602 - MINNICH WILLY
- [X] EP 0218987 A2 19870422 - DYCKERHOFF & WIDMANN AG
- [X] US 3665717 A 19720530 - SWEENEY GERALD T, et al
- [A] US 3638435 A 19720201 - MASON EDWARD E
- [A] FR 2600687 A1 19871231 - SAUTEREAU ROLAND [FR]
- [A] GB 2017790 A 19791010 - TRANSPORT SECRETARY OF STATE F
- [A] FR 2335319 A1 19770715 - INTRAFOR COFOR [FR]
- [X] PATENT ABSTRACTS OF JAPAN, Band 6, Nr. 263 (M-181)[1141], 22. Dezember 1982; & JP-A-57 155 427 (KUBOTA TEKKO K.K.) 25-09-1982

Cited by

FR2841273A1

Designated contracting state (EPC)

AT BE CH DE ES FR GB IT LI LU NL SE

DOCDB simple family (publication)

EP 0341568 A2 19891115; EP 0341568 A3 19891220; EP 0341568 B1 19920102; AT E71165 T1 19920115; DE 58900651 D1 19920213

DOCDB simple family (application)

EP 89108024 A 19890503; AT 89108024 T 19890503; DE 58900651 T 19890503