

Title (en)
WINDOW OR DOOR FRAME TO BE INSTALLED IN A WALL OPENING

Publication
EP 0341635 B1 19920805 (DE)

Application
EP 89108257 A 19890508

Priority
CH 179788 A 19880511

Abstract (en)
[origin: EP0341635A1] For the purpose of fitting to the inside width of the wall opening (10), the door frame (14), which comprises metal sections (12) and is installed in a wall opening (10), has a compensating bar (16) which can be pressed against the wall opening relatively to the metal sections (12) on each of its limbs (18, 20, 22). The compensating rails (16) are installed in openings extending in the longitudinal direction of the metal sections (12) and are arranged to be movable in the transverse direction. For the purpose of pressing on, use is made of clamping screws which are accessible through holes from the inside of the door frame (14). To fill in the two upper corners of the door frame (14), corner pieces (50) are installed in the mutually adjacent ends of the compensating bars (16), which are composed of square hollow sections. Such a door frame, which can also be designed as a window frame, facilitates the fitting to the particular wall opening with little input of labour. <IMAGE>

IPC 1-7
E06B 1/60

IPC 8 full level
E06B 1/60 (2006.01)

CPC (source: EP)
E06B 1/6076 (2013.01)

Cited by
EP1273751A1; GB2334742A; GB2334742B; WO9717521A1

Designated contracting state (EPC)
AT BE CH DE ES FR GB IT LI LU NL SE

DOCDB simple family (publication)
EP 0341635 A1 19891115; EP 0341635 B1 19920805; AT E79150 T1 19920815; CH 675613 A5 19901015; DE 58901971 D1 19920910; ES 2034480 T3 19930401

DOCDB simple family (application)
EP 89108257 A 19890508; AT 89108257 T 19890508; CH 179788 A 19880511; DE 58901971 T 19890508; ES 89108257 T 19890508