

Title (en)

USE OF CARBON MATERIALS

Publication

EP 0342542 B1 19930804 (EN)

Application

EP 89108592 A 19890512

Priority

JP 11748788 A 19880514

Abstract (en)

[origin: EP0342542A2] A process for producing a reformed pitch useful for various carbon materials is provided. This process comprises mixing a pitch having a ratio of aromatic hydrocarbon fa of 0.6 or more with a Lewis acid and a co-solvent so as to give a mol ratio of the said Lewis acid to the said pitch in the range of 0.3 SIMILAR 5.0 and a mol ratio of the said co-solvent to the said pitch in the range of ratio of 2.5 SIMILAR 50, reacting the mixture at a temperature of 100 SIMILAR 300 DEG C and removing the Lewis acid and the co-solvent from the reaction product. Meso-Carbon microbeads having a uniform diameter of 20 mu m or less can be produced at a high yield of 60% or more by heat treating the reformed pitch at 200 SIMILAR 380 DEG C to produce the optically anisotropic small spheres and separating them from an optically isotropic matrix.

IPC 1-7

C10C 3/00; D01F 9/14

IPC 8 full level

C10B 55/00 (2006.01); **C10C 3/00** (2006.01); **C10C 3/02** (2006.01); **C10C 3/10** (2006.01); **C10C 3/14** (2006.01); **D01F 9/145** (2006.01)

CPC (source: EP)

C10C 3/002 (2013.01); **C10C 3/14** (2013.01); **D01F 9/145** (2013.01)

Cited by

CN105238428A

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

EP 0342542 A2 19891123; EP 0342542 A3 19900214; EP 0342542 B1 19930804; DE 68908004 D1 19930909; DE 68908004 T2 19940105;
DE 68917318 D1 19940908; DE 68917318 T2 19950209; EP 0456278 A1 19911113; EP 0456278 B1 19940803; JP 2630466 B2 19970716;
JP H0249095 A 19900219

DOCDB simple family (application)

EP 89108592 A 19890512; DE 68908004 T 19890512; DE 68917318 T 19890512; EP 91111551 A 19890512; JP 11746889 A 19890512