

Title (en)

OPTICAL SENSOR OF THE PASSIVE OPTODE KIND, ESPECIALLY FOR USE IN SPECTRO FLUORIMETRY AND RAMAN SPECTROMETRY

Publication

EP 0343037 B1 19920722 (FR)

Application

EP 89401293 A 19890510

Priority

FR 8806401 A 19880511

Abstract (en)

[origin: EP0343037A1] It comprises a first light guide (14) and a second light guide (22) which surrounds the first. One of the two guides conveys to a medium to be analyzed a first light for exciting this medium which then emits a second light. A perforated mirror (38) placed opposite the guides reflects the second light so that it is captured by this other guide, whilst not allowing the first light to be captured by it. The mirror is also such that, in a neighbourhood of the sensor-medium interface closest to the guides, and in any plane cross-section of the medium, contained in this neighbourhood and perpendicular to the guides, the surface traversed by the first light is substantially equal to that which emits a quantity of second light which is captured by the said other guide. <IMAGE>

IPC 1-7

G01N 21/51; **G01N 21/64**

IPC 8 full level

G01N 21/64 (2006.01); **G01N 21/65** (2006.01); **G01N 21/85** (2006.01)

CPC (source: EP)

G01N 21/64 (2013.01); **G01N 21/65** (2013.01); **G01N 21/8507** (2013.01); **G01N 2021/6434** (2013.01); **G01N 2021/6484** (2013.01); **G01N 2021/656** (2013.01)

Cited by

DE19845553C2; EP0459846A3; FR2661499A1; US6696939B2

Designated contracting state (EPC)

BE DE GB

DOCDB simple family (publication)

EP 0343037 A1 19891123; **EP 0343037 B1 19920722**; DE 68902179 D1 19920827; DE 68902179 T2 19930114; FR 2631444 A1 19891117; FR 2631444 B1 19900713; JP H01321341 A 19891227

DOCDB simple family (application)

EP 89401293 A 19890510; DE 68902179 T 19890510; FR 8806401 A 19880511; JP 11621089 A 19890511