

Title (en)

MACHINE FOR CUTTING TAPE FROM A TUBULAR FABRIC

Publication

EP 0343498 B1 19920325 (DE)

Application

EP 89108876 A 19890517

Priority

CH 202188 A 19880527

Abstract (en)

[origin: JPH02152792A] PURPOSE: To precisely maintain the width of a band along the band by providing a regulating means to regulate the stroke of a jacket member of a feeding cylinder based on the detected signal of a second sensing means. CONSTITUTION: When the angle of a bracket 8 relative to a turn table is changed by the twisting of a textile, the change is sensed by a sensing member 9, the corresponding control signal transmitted to a first sensing means 2 is transmitted to a control apparatus 10, the peripheral speed of a feeding cylinder 3 to the rotational speed of a turn table 1 is controlled, and the twisting of the textile is controlled thereby. In addition, the position of an upper edge of the textile to be respectively cut by a second sensing means 6 is sensed, and the detected signal is inputted in a regulating device 15. The cutting width of a band is regulated by controlling the stroke of jacket members 4, 5 by the regulating device 15.

IPC 1-7

B26D 3/16; B26D 7/26; D06H 7/12

IPC 8 full level

B26D 1/24 (2006.01); **B26D 3/16** (2006.01); **B26D 7/26** (2006.01); **D06H 7/12** (2006.01)

CPC (source: EP US)

B26D 3/162 (2013.01 - EP US); **B26D 7/2635** (2013.01 - EP US); **D06H 7/12** (2013.01 - EP US); **Y10S 83/935** (2013.01 - EP US);
Y10T 29/1156 (2015.01 - EP US); **Y10T 29/1169** (2015.01 - EP US); **Y10T 83/141** (2015.04 - EP US); **Y10T 83/323** (2015.04 - EP US);
Y10T 83/783 (2015.04 - EP US)

Designated contracting state (EPC)

CH DE ES FR GB IT LI SE

DOCDB simple family (publication)

EP 0343498 A1 19891129; EP 0343498 B1 19920325; CH 677942 A5 19910715; DE 58901016 D1 19920430; ES 2031656 T3 19921216;
JP 2667003 B2 19971022; JP H02152792 A 19900612; US 5083351 A 19920128

DOCDB simple family (application)

EP 89108876 A 19890517; CH 202188 A 19880527; DE 58901016 T 19890517; ES 89108876 T 19890517; JP 12904189 A 19890524;
US 35547689 A 19890522