

Title (en)

GLOW PLUG FOR MOTOR VEHICLE HEATERS USING LIQUID FUEL AND OPERATING INDEPENDENTLY FROM THE ENGINE

Publication

EP 0343551 B1 19931006 (DE)

Application

EP 89109141 A 19890520

Priority

DE 3817723 A 19880525

Abstract (en)

[origin: EP0343551A2] In the case of floor-mounted heaters for motor vehicles, in order to be able to use standard glow plugs irrespective of the operating voltage (12 volts or 24 volts), without having to resort to upstream resistors for certain operating voltages, a glow plug has two heating rods and three electrical connection contacts so that, depending on the operating voltage, the heating rods can either be connected in parallel (for a 12 volt installation) or connected in series (for example, for a 24 volt installation) and the same electrical (and thermal) output is always achieved.
<IMAGE>

IPC 1-7

F23Q 7/08

IPC 8 full level

F23Q 7/00 (2006.01); **F23Q 7/08** (2006.01)

CPC (source: EP)

F23Q 7/001 (2013.01); **F23Q 7/08** (2013.01)

Designated contracting state (EPC)

DE FR GB IT SE

DOCDB simple family (publication)

EP 0343551 A2 19891129; EP 0343551 A3 19900516; EP 0343551 B1 19931006; CA 1318944 C 19930608; CS 276753 B6 19920812; CS 8903070 A2 19911217; DE 3817723 A1 19891130; DE 3817723 C2 19900222; DE 58905806 D1 19931111

DOCDB simple family (application)

EP 89109141 A 19890520; CA 600266 A 19890519; CS 307089 A 19890522; DE 3817723 A 19880525; DE 58905806 T 19890520