

Title (en)

PROCESS AND DEVICE FOR REGULATING THE WIDTH OF THE YARN SET IN WARPING MACHINES

Publication

EP 0344115 A3 19910417 (DE)

Application

EP 89810370 A 19890519

Priority

CH 203688 A 19880527

Abstract (en)

[origin: EP0344115A2] The width (11) of the yarn set (10) of a warping machine (2) is continuously monitored with the aid of a line camera (25). The measured width is compared in a processor (32) with a stored target value, and deviations form a control signal which activates a control motor (35) on the warp reed (9). This ensures continuous yarn set width control at full winding speed. <IMAGE>

IPC 1-7

D02H 3/00

IPC 8 full level

D02H 13/00 (2006.01); **D02H 3/00** (2006.01)

CPC (source: EP US)

D02H 3/02 (2013.01 - EP US)

Citation (search report)

- [AD] EP 0174631 A2 19860319 - MITSUBISHI ACETATE CO LTD [JP], et al
- [A] DE 3435391 A1 19850425 - ASEA AB [SE]
- [AD] DE 3527424 A1 19870205 - HACOBA TEXTILMASCHINEN [DE]
- [A] US 4549453 A 19851029 - YAZAKI SUSUMU [JP], et al
- [A] US 4021031 A 19770503 - MEIHOFER EDWARD F, et al
- [X] TEXTIL PRAXIS INTERNATIONAL, Band 41, Nr. 11, November 1986, Seiten 1184-1191, Leinfelden DE; H. THEIHSEN: "Konusschärmachine USK mit patentiertem Schärverfahren für vollelektronische Messung des Schärtischvorschubes"

Cited by

EP0531737A1; EP0434610A1; CN107523914A; EP3181743A1

Designated contracting state (EPC)

BE CH DE ES FR IT LI

DOCDB simple family (publication)

EP 0344115 A2 19891129; EP 0344115 A3 19910417; CH 678196 A5 19910815; JP H0226948 A 19900129; US 4974301 A 19901204

DOCDB simple family (application)

EP 89810370 A 19890519; CH 203688 A 19880527; JP 13446189 A 19890526; US 35439989 A 19890519