

Title (en)
BUCKLE FOR A SAFETY BELT

Publication
EP 0345113 B1 19921230 (FR)

Application
EP 89401363 A 19890517

Priority
FR 8807370 A 19880602

Abstract (en)
[origin: US4916780A] The buckle comprises a latch (10) interacting with a keeper consisting of a base (20), of an ejecting guide bolt (30), of an actuating button (50), of a protective casing (60) and of a securing connection (70), among other things. Means (40) having an insertion and retention system (301, 302, 303, 304), a safeguarding arrangement (410, 420) and a guide device (430, 440) make it possible to safeguard the locked latch in the keeper after it has been introduced into a channel (200) and a receptacle (300) which are oblique relative to one another. The invention is used on safety belts for motor vehicles.

IPC 1-7
A44B 11/25

IPC 8 full level
A44B 11/25 (2006.01)

CPC (source: EP KR US)
A44B 11/00 (2013.01 - KR); **A44B 11/2523** (2013.01 - EP US); **A44B 11/2565** (2013.01 - EP US); **Y10T 24/45654** (2015.01 - EP US); **Y10T 24/4567** (2015.01 - EP US)

Designated contracting state (EPC)
DE ES GB IT SE

DOCDB simple family (publication)
EP 0345113 A1 19891206; **EP 0345113 B1 19921230**; DE 68904120 D1 19930211; DE 68904120 T2 19930819; ES 2036814 T3 19930601; FR 2632166 A1 19891208; FR 2632166 B1 19900921; KR 900000045 A 19900130; KR 960013456 B1 19961005; US 4916780 A 19900417

DOCDB simple family (application)
EP 89401363 A 19890517; DE 68904120 T 19890517; ES 89401363 T 19890517; FR 8807370 A 19880602; KR 890006876 A 19890523; US 35417689 A 19890519