

Title (en)

METHOD FOR INSTALLING A LIFT OR LOAD ELEVATOR INSIDE A BUILDING, ASSEMBLY JIGS USED THEREFOR, LIFT OR LOAD ELEVATOR THUS OBTAINED

Publication

EP 0345322 B1 19920422 (FR)

Application

EP 89900259 A 19881128

Priority

FR 8716497 A 19871127

Abstract (en)

[origin: WO8904807A1] The present invention relates to a method for installing a lift or a load elevator inside a building, the assembly jigs used for such purpose and the lift or load elevator thus obtained. According to this method, the assembly jigs (1) are successively arranged in place, which jigs comprise lift elements (guiding rails (13, 15) and doors which are prepositioned in the support shield (5). These elements are secured without adjustment to the supporting shield and the jig is removed.

IPC 1-7

B66B 19/00

IPC 8 full level

B66B 7/00 (2006.01); **B66B 19/00** (2006.01)

CPC (source: EP US)

B66B 19/00 (2013.01 - EP US); **B66B 19/002** (2013.01 - EP US)

Cited by

EP2019074A1

Designated contracting state (EPC)

CH DE GB IT LI

DOCDB simple family (publication)

WO 8904807 A1 19890601; AU 2792389 A 19890614; AU 609925 B2 19910509; DE 3870446 D1 19920527; EP 0345322 A1 19891213; EP 0345322 B1 19920422; FI 893449 A0 19890717; FI 893449 A 19890717; FI 92315 B 19940715; FI 92315 C 19941025; FR 2623787 A1 19890602; FR 2623787 B1 19900511; JP 2664789 B2 19971022; JP H02502276 A 19900726; US 5014822 A 19910514

DOCDB simple family (application)

FR 8800581 W 19881128; AU 2792389 A 19881128; DE 3870446 T 19881128; EP 89900259 A 19881128; FI 893449 A 19890717; FR 8716497 A 19871127; JP 50035988 A 19881128; US 39391189 A 19890726