

Title (en)  
CURRENT CONDUCTING SYSTEM

Publication  
**EP 0346348 B1 19911016 (DE)**

Application  
**EP 88901244 A 19880119**

Priority  
• DE 3701449 A 19870120  
• DE 3800358 A 19880108

Abstract (en)  
[origin: WO8805613A1] A current conducting system, in particular for lighting systems of the most varied types, has a current conducting rod, at least 50 % of the cross-section area thereof being occupied by at least two mutually-isolated metallic current conductors. Thus it is possible to work with high current densities, especially when using the current conducting system in the low voltage range. The current conducting rod is preferably round, so that holding clamps that carry electric consumers such as lamps, fans, etc. can be rotated thereon. Advantageous implementations of the holders allow the holders to swing as well, so that the user is virtually free to arrange and position the electric consumer as he wishes.

IPC 1-7  
**H01R 25/14**

IPC 8 full level  
**H01R 25/14** (2006.01)

CPC (source: EP)  
**H01R 25/147** (2013.01)

Designated contracting state (EPC)  
AT CH DE FR GB IT LI

DOCDB simple family (publication)  
**WO 8805613 A1 19880728**; AT E68635 T1 19911115; AU 1227988 A 19880810; CA 1297548 C 19920317; DE 3800358 A1 19880804; DE 3865673 D1 19911121; EP 0346348 A1 19891220; EP 0346348 B1 19911016

DOCDB simple family (application)  
**EP 8800033 W 19880119**; AT 88901244 T 19880119; AU 1227988 A 19880119; CA 556975 A 19880120; DE 3800358 A 19880108; DE 3865673 T 19880119; EP 88901244 A 19880119