

Title (en)

RODLESS ACTUATOR WITH A STROKE-LIMITING DEVICE

Publication

**EP 0346504 B1 19920122 (DE)**

Application

**EP 88109346 A 19880611**

Priority

EP 88109346 A 19880611

Abstract (en)

[origin: EP0346504A1] A rodless actuator with a stroke limiting device. There is a cylinder (1) which contains a cylinder tube (2) in which a displaceable piston actuated by pressure medium and designed as a drive part (4) is located. It is provided with an inner driving-magnet arrangement (14). Located on the outside on the cylinder tube (2) is an output part (10) provided with an outer driving-magnet arrangement (15), and the two parts (4, 10) are magnetically coupled to one another. The stroke limiting device (17) is arranged on the outside on the cylinder (1) and co-operates with the output part (10). <IMAGE>

IPC 1-7

**F15B 15/08; F15B 15/24**

IPC 8 full level

**F15B 15/08** (2006.01); **F15B 15/24** (2006.01)

CPC (source: EP)

**F15B 15/086** (2013.01); **F15B 15/24** (2013.01)

Cited by

DE10107474B4; FR2687134A1; KR20030069687A; DE10017959C2; GB2397344A; GB2397344B; US6905108B2; WO03042549A1; US6308821B1; WO2014022871A1; WO2010026399A1

Designated contracting state (EPC)

AT BE CH DE ES FR GB GR IT LI NL SE

DOCDB simple family (publication)

**EP 0346504 A1 19891220; EP 0346504 B1 19920122**; AT E72022 T1 19920215; DE 3868058 D1 19920305; ES 2028184 T3 19920701; GR 3003792 T3 19930316

DOCDB simple family (application)

**EP 88109346 A 19880611**; AT 88109346 T 19880611; DE 3868058 T 19880611; ES 88109346 T 19880611; GR 920400230 T 19920212