

Title (en)

SEAFFOLD PLANK

Publication

EP 0347476 B1 19920902 (DE)

Application

EP 88109810 A 19880620

Priority

EP 88109810 A 19880620

Abstract (en)

[origin: EP0347476A1] To allow a plank for scaffolding in the form of an elongated hollow metal profile (1) to be subjected to high stresses, it is proposed that a closure profile (17) is pushed into each of the front ends (12, 13), and that the holes (6, 7, 8, 9), serving for fastening to the scaffolding, are formed by flow forming in such a way that the metal of the hollow metal profile (1) and of the closure profile (17) is fused together in the region of the to be formed holes (6, 7, 8, 9) by flow forming into cylindrical bushes (28, 29). <IMAGE>

IPC 1-7

E04G 1/15

IPC 8 full level

B21C 37/29 (2006.01); **E04G 1/15** (2006.01)

CPC (source: EP)

B21C 37/298 (2013.01); **B21J 5/066** (2013.01); **E04G 1/152** (2013.01); **E04G 1/154** (2013.01); **E04G 2001/158** (2013.01)

Cited by

CN115977360A; CN107130807A; US5555955A; CN115176061A; US6076991A; US7090053B2; AT1028U1; US6105723A; US5882136A; US7401556B2; WO2021046614A1; US7584824B2; US7188707B2

Designated contracting state (EPC)

AT BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

EP 0347476 A1 19891227; **EP 0347476 B1 19920902**; AT E80194 T1 19920915; DE 3874330 D1 19921008; ES 2035163 T3 19930416; GR 3005604 T3 19930607

DOCDB simple family (application)

EP 88109810 A 19880620; AT 88109810 T 19880620; DE 3874330 T 19880620; ES 88109810 T 19880620; GR 920401930 T 19920903