

Title (en)

Device for suppression of leakage of magnetic flux in display apparatus.

Title (de)

Vorrichtung zum Eliminieren von magnetischen Streufeldern in Bildwiedergabeeinrichtungen.

Title (fr)

Dispositif d'élimination de champs de fuite magnétiques dans des dispositifs de visualisation.

Publication

**EP 0348205 B1 19951011 (EN)**

Application

**EP 89306338 A 19890623**

Priority

JP 15641188 A 19880624

Abstract (en)

[origin: EP0348205A2] There is disclosed a device for suppression of leakage flux from a deflecting yoke, which is assembled in a display apparatus having a cathode ray tube (a CRT) for displaying an image by radiation of an electron beam from an electron gun to a fluorescent display surface, and the deflecting yoke having some coils arranged at a rear portion of the CRT and for deflecting the electron beam. The device comprises two cancelling wires (5a, 5b) which are disposed at the inner sides of upper and lower ends in front of the CRT and connected in parallel for generating cancellation flux to negate the leakage flux from the coils, and a control circuit (10) for controlling the cancellation flux generated by the wires in the manner that the leakage flux from a face-plate of the CRT is reduced by regulation of current value supplied to the wires.

IPC 1-7

**H01J 29/00**; **H01J 29/76**

IPC 8 full level

**G09G 1/04** (2006.01); **H01J 29/00** (2006.01); **H01J 29/76** (2006.01); **H04N 3/16** (2006.01)

CPC (source: EP)

**H01J 29/003** (2013.01); **H01J 2229/0015** (2013.01)

Cited by

US5959392A; US5200673A; EP0547856A1; US5485056A; EP0466064A1; WO9623315A1

Designated contracting state (EPC)

DE GB SE

DOCDB simple family (publication)

**EP 0348205 A2 19891227**; **EP 0348205 A3 19900613**; **EP 0348205 B1 19951011**; DE 68924500 D1 19951116; DE 68924500 T2 19960321; JP H027334 A 19900111

DOCDB simple family (application)

**EP 89306338 A 19890623**; DE 68924500 T 19890623; JP 15641188 A 19880624