

Title (en)  
LACING FASTENING FOR SHOES

Publication  
**EP 0348284 B1 19920610 (FR)**

Application  
**EP 89401709 A 19890616**

Priority  
FR 8808460 A 19880623

Abstract (en)  
[origin: EP0348284A1] A lacing fastening comprises, along the edge of each of two parts which are to be brought together and/or clamped one against the other, a succession of eyelets (4) through which, in succession, passes the lacing (3), the two sets of opposing eyelets (4) being situated in a single lacing plane (P) likewise containing the lacing (3) passing through the successive eyelets (4). <??>In order to retain the lacing as well as possible, particularly when it is loosened, each eyelet (4) is contained within a plane (P1) which is inclined relative to the lacing plane (P) at an angle such that, on passing through the eyelet (4), the lacing is in contact with the latter solely at two opposite points (A; B) which are spaced apart in the longitudinal direction of the lacing (3). <IMAGE>

IPC 1-7  
**A43C 5/00**

IPC 8 full level  
**A43B 3/00** (2006.01); **A43B 23/02** (2006.01); **A43C 1/04** (2006.01); **A43C 3/00** (2006.01); **A43C 5/00** (2006.01)

CPC (source: EP US)  
**A43C 1/04** (2013.01 - EP US); **A43C 5/00** (2013.01 - EP US); **Y10T 24/3737** (2015.01 - EP US); **Y10T 24/3742** (2015.01 - EP US)

Designated contracting state (EPC)  
DE FR GB IT SE

DOCDB simple family (publication)  
**EP 0348284 A1 19891227**; **EP 0348284 B1 19920610**; DE 68901749 D1 19920716; DE 68901749 T2 19930128; FR 2633163 A1 19891229; FR 2633163 B1 19901012; JP H0241101 A 19900209; JP H0693848 B2 19941124; US 4958418 A 19900925

DOCDB simple family (application)  
**EP 89401709 A 19890616**; DE 68901749 T 19890616; FR 8808460 A 19880623; JP 15594389 A 19890620; US 36774889 A 19890619