

Title (en)

PROCESS FOR MAKING A TENSION MEMBER ADAPTED TO BE ANCHORED IN THE GROUND

Publication

**EP 0350454 B1 19930526 (DE)**

Application

**EP 89810506 A 19890704**

Priority

CH 258188 A 19880706

Abstract (en)

[origin: JPH0249816A] PURPOSE: To impart high ductility to a tension part by precutting the outer members of the tension part, and situating a point of severance at the end of a pressure support element. CONSTITUTION: One outer member 3' of outer members 3 disposed around the central member 2 of a tension part 1 is cut at the point of severance 4. After cutting, a tubular support element 5 is slid over the tension part 1 until it covers the point of severance 4. Then a force is radially inwardly applied to the support element 5 to press the tension part 1. In this case, the point of severance 4 is situated in the range of half the length L of the support member 5, and in front of or behind the end of the supporting element 5.

IPC 1-7

**E02D 5/74; E02D 5/76**

IPC 8 full level

**E02D 5/80** (2006.01); **E02D 5/74** (2006.01); **E02D 5/76** (2006.01)

CPC (source: EP KR US)

**E02D 5/765** (2013.01 - EP US); **E02D 5/80** (2013.01 - KR)

Cited by

CN104563110A; EP0638689A1; FR2708948A1

Designated contracting state (EPC)

AT CH DE FR GB LI SE

DOCDB simple family (publication)

**EP 0350454 A2 19900110; EP 0350454 A3 19900418; EP 0350454 B1 19930526**; AT E89882 T1 19930615; AU 3715489 A 19900111; AU 639355 B2 19930722; AU 8142791 A 19911010; DE 58904466 D1 19930701; HK 130094 A 19941202; JP 2846661 B2 19990113; JP H0249816 A 19900220; KR 900001934 A 19900227; MY 108500 A 19961031; US 5113634 A 19920519

DOCDB simple family (application)

**EP 89810506 A 19890704**; AT 89810506 T 19890704; AU 3715489 A 19890628; AU 8142791 A 19910729; DE 58904466 T 19890704; HK 130094 A 19941124; JP 17133189 A 19890704; KR 890009581 A 19890706; MY PI19890853 A 19890623; US 37077189 A 19890623