

Title (en)

SHEET FINISHER

Publication

EP 0350926 A3 19910529 (EN)

Application

EP 89112864 A 19890713

Priority

- JP 17388488 A 19880714
- JP 17388588 A 19880714
- JP 17388688 A 19880714
- JP 17388788 A 19880714
- JP 17388888 A 19880714
- JP 17388988 A 19880714
- JP 17389088 A 19880714

Abstract (en)

[origin: EP0350926A2] The sheet finisher includes a predetermined folding mode for receiving a sheet from a copy machine and which features plurality of transfer guides (104,110) through which the sheet received from the copy machine are selectively transferred; switching flappers (122) for switching the flow of the sheet between guides (104,110), a temporary holding guide (106) in which the leading end portion of sheet can be temporarily inserted; a sheet folding arrangement including press roller pairs (130,132) for folding the sheet; a sheet discharge angle control device which varies the angle at which the sheet are discharged onto an upper tray (18) in accordance with the folding mode that is being used; a tray shift mechanism (300) for moving the tray left and right so as to stack the sheets which are discharged thereonto in a classifying manner; a friction roller for moving a predetermined corner of each of the sheets into a preselected corner of the tray (18); a fastening device for fastening the sheets which have been maneuvered into the preselected corner by the friction roller; a tray rise mechanism for changing the distance between the upper surface of the tray (18) and the level at which the sheets are discharged; an escape mechanism which drops processed stacks of sheets from the upper tray (18) into a lower one (20); and a tray angle varying mechanism for changing the angle of the lower tray (20) when the stacks are dropped theretowards.

IPC 1-7

B65H 45/12; B65H 29/22; B65H 33/08; B65H 9/16; B42B 4/00

IPC 8 full level

B42B 4/00 (2006.01); **B65H 9/16** (2006.01); **B65H 29/22** (2006.01); **B65H 37/04** (2006.01); **B65H 45/14** (2006.01)

CPC (source: EP US)

B42B 4/00 (2013.01 - EP US); **B65H 9/166** (2013.01 - EP US); **B65H 29/22** (2013.01 - EP US); **B65H 37/04** (2013.01 - EP US);
B65H 45/142 (2013.01 - EP US); **B65H 2405/351** (2013.01 - EP US)

Citation (search report)

- [A] US 4717134 A 19880105 - IIDA NORIYOSHI [JP], et al
- [X] EP 0266739 A2 19880511 - CANON KK [JP]
- [A] EP 0113122 A1 19840711 - FUJI PHOTO FILM CO LTD [JP]
- [A] US 4640611 A 19870203 - OHDAKE EISHU [JP], et al
- [A] EP 0033835 A1 19810819 - IBM [US]
- [A] JP S62244869 A 19871026 - RICOH KK
- [A] PATENT ABSTRACTS OF JAPAN, vol. 11, no. 6 (M-551), 8th January 1987; & JP-A-61 183 055 (FUJI XEROX CO., LTD) 15-08-1986
- [A] PATENT ABSTRACTS OF JAPAN, vol. 9, no. 135 (M-386)[1858], 11th June 1985; & JP-A-60 015 357 (FUJI XEROX K.K.) 26-01-1985
- [A] PATENT ABSTRACTS OF JAPAN, vol. 12, no. 260 (M-720)[3107], 21st July 1988; & JP-A-63 041 350 (CANON INC.) 22-02-1988
- [A] PATENT ABSTRACTS OF JAPAN, vol. 9, no. 279 (M-427)[2002], 7th November 1985; & JP-A-60 122 662 (CANON K.K.) 01-07-1985

Cited by

CN110282482A

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

EP 0350926 A2 19900117; EP 0350926 A3 19910529; EP 0350926 B1 19940622; DE 68916327 D1 19940728; DE 68916327 T2 19950302;
US 5020785 A 19910604; US 5129640 A 19920714

DOCDB simple family (application)

EP 89112864 A 19890713; DE 68916327 T 19890713; US 37805189 A 19890711; US 70929591 A 19910603