

Title (en)

PISTONS PISTONS

Publication

EP 0351976 A3 19900502 (EN)

Application

EP 89306758 A 19890704

Priority

GB 8816983 A 19880716

Abstract (en)

[origin: EP0351976A2] A piston (10) for a reciprocating machine includes a split piston ring (13) which is located in a circumferential groove (12) in the cylindrical wall of the piston (10). The piston (10) is adapted to be located in a cylindrical bore (11) so that the piston ring (13) sealingly engages the bore (11) with a gap (14) between its ends, the gap (14) being fully underlaid and sealed by a contiguous unbroken annular supporting ring (15), a spring (16) being provided to maintain the ends of the piston ring (13) in engagement with the supporting ring (15).

IPC 1-7

F02F 3/00; F16J 9/14

IPC 8 full level

F02F 5/00 (2006.01); **F02F 3/00** (2006.01); **F16J 1/00** (2006.01); **F16J 9/14** (2006.01); **F16J 9/16** (2006.01); **F16J 9/24** (2006.01)

CPC (source: EP US)

F02F 3/00 (2013.01 - EP US); **F16J 9/16** (2013.01 - EP US); **F16J 9/24** (2013.01 - EP US); **F05C 2251/042** (2013.01 - EP US)

Citation (search report)

- [X] FR 838056 A 19390227 - HAREL MECHANICAL PROCESSES LTD
- [A] GB 191321665 A 19140730 - BOYLE JOHN, et al
- [A] US 1699135 A 19290115 - CRONIN JAMES A

Cited by

EP0863302A1; US5996545A; AT519652A4; AT519652B1; EP2369181A1; ITMO20100060A1; WO9512755A1

Designated contracting state (EPC)

DE FR GB IT SE

DOCDB simple family (publication)

EP 0351976 A2 19900124; EP 0351976 A3 19900502; GB 8816983 D0 19880817; JP H0262479 A 19900302; US 5072653 A 19911217

DOCDB simple family (application)

EP 89306758 A 19890704; GB 8816983 A 19880716; JP 18239289 A 19890714; US 37806089 A 19890711