

Title (en)
METHOD OF MANUFACTURING A SCINTILLATOR, AND SCINTILLATOR SO OBTAINED

Publication
EP 0352152 B1 19930512 (FR)

Application
EP 89401788 A 19890623

Priority
FR 8809938 A 19880722

Abstract (en)
[origin: EP0352152A1] Improvement to the manufacture of a scintillator especially for the input screen of a radiological image-intensifier tube. <??>According to the invention the substrate (11) on which a layer of scintillating material (12) such as caesium iodide deposited in the form of needles (13b) is grown is subjected to a treatment ending in the formation of a surface quality or of an alveolate structure (15) resulting in the formation of finer needles. <??>The reduction in the average diameter of the needles is reflected in an improvement in the resolution of the device. <IMAGE>

IPC 1-7
G21K 4/00; **H01J 9/12**; **H01J 29/38**

IPC 8 full level
H01J 9/233 (2006.01); **G21K 4/00** (2006.01); **H01J 9/12** (2006.01); **H01J 29/38** (2006.01); **H01J 31/50** (2006.01)

CPC (source: EP US)
G21K 4/00 (2013.01 - EP US); **H01J 9/12** (2013.01 - EP US); **H01J 29/385** (2013.01 - EP US)

Cited by
EP1158540A1; EP1113458A1; DE4124875A1; US7161160B2

Designated contracting state (EPC)
DE FR GB NL

DOCDB simple family (publication)
EP 0352152 A1 19900124; **EP 0352152 B1 19930512**; DE 68906478 D1 19930617; DE 68906478 T2 19930909; FR 2634562 A1 19900126; FR 2634562 B1 19900907; JP 3084713 B2 20000904; JP H02223129 A 19900905; US 4985633 A 19910115; US 5449449 A 19950912

DOCDB simple family (application)
EP 89401788 A 19890623; DE 68906478 T 19890623; FR 8809938 A 19880722; JP 18758189 A 19890721; US 36532694 A 19941228; US 38186289 A 19890719