

Title (en)
THERMAL DYE RIBBON AND METHOD OF PREPARATION

Publication
EP 0352525 A3 19901107 (DE)

Application
EP 89112424 A 19890707

Priority
DE 3825438 A 19880727

Abstract (en)
[origin: EP0352525A2] A thermal ink ribbon, especially a thermal carbon ribbon, is described which has a conventional support and a layer of a melt-on ink formed on one side of the support, a separating layer being provided between the surface of the support and the layer of melt-on ink. The special characteristic of this thermal ink ribbon is that the separating layer contains water-releasing agents dispersed in a binder. Such a thermal ink ribbon is distinguished in that the melt-on ink can be readily and completely detached in the area of the embossed thermal symbol during the thermal printing process.

IPC 1-7
B41M 5/26

IPC 8 full level
B41J 31/00 (2006.01); **B41M 5/26** (2006.01); **B41M 5/382** (2006.01); **B41M 5/42** (2006.01); **B41M 5/40** (2006.01); **B41M 5/44** (2006.01)

CPC (source: EP US)
B41M 5/42 (2013.01 - EP US); **B41M 5/426** (2013.01 - EP US); **B41M 5/44** (2013.01 - EP US); **B41M 2205/30** (2013.01 - EP US)

Citation (search report)
• [A] EP 0228065 A2 19870708 - EASTMAN KODAK CO [US]
• [A] PATENT ABSTRACTS OF JAPAN vol. 11, no. 295 (M-626)(2742) 24 September 1987, & JP-A-62 87391 (BROTHERS IND LTD) 21 April 1987,

Cited by
EP0513800A1

Designated contracting state (EPC)
AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)
EP 0352525 A2 19900131; **EP 0352525 A3 19901107**; **EP 0352525 B1 19930421**; AT E88416 T1 19930515; DE 3825438 A1 19900215; DE 3825438 C2 19900705; DE 58904121 D1 19930527; JP H0274375 A 19900314; JP H0775900 B2 19950816; US 5106217 A 19920421

DOCDB simple family (application)
EP 89112424 A 19890707; AT 89112424 T 19890707; DE 3825438 A 19880727; DE 58904121 T 19890707; JP 19278489 A 19890727; US 55379489 A 19890726