

Title (en)

METHOD FOR ELIMINATING AND AVOIDING WORK INTERRUPTIONS CAUSED BY THE TYING MEANS IN TYING MACHINES FOR PACKAGES

Publication

EP 0353505 B1 19920617 (DE)

Application

EP 89112739 A 19890712

Priority

DE 3825668 A 19880728

Abstract (en)

[origin: EP0353505A1] Claimed and described is a working method for eliminating work interruptions caused by the tying means in tying machines, which is characterised in that the tying means located in the machine are withdrawn from the tying means coil moved counter to the feeding direction of the tying means in the event of a malfunction, or is automatically withdrawn from the machine "at the press of a button". As a result, intervention in the machine, and hence in a packaging line in which the machine is integrated, is no longer necessary. The fault can be eliminated from the outside, for instance by cutting the destroyed start of the tape and renewed introduction into the machine. A working method for preventing work interruptions caused by tying means is characterised in that, in the event of a mains interruption or an interruption in the operation of the machine exceeding a preselected time period, from the tying means coil then moved automatically counter to the feeding direction of the tying means, the tying means is at least withdrawn from the tying means store.

IPC 1-7

B65B 13/18

IPC 8 full level

B65B 13/18 (2006.01); **B65B 57/02** (2006.01)

CPC (source: EP)

B65B 13/18 (2013.01)

Cited by

EP1403184A1; DE19854680B4; US6848239B2; US7428866B2; WO2005095214A1

Designated contracting state (EPC)

CH DE FR GB IT LI NL

DOCDB simple family (publication)

EP 0353505 A1 19900207; **EP 0353505 B1 19920617**; DE 3825668 C1 19900215; DE 58901679 D1 19920723; JP H02180109 A 19900713; JP H0723134 B2 19950315

DOCDB simple family (application)

EP 89112739 A 19890712; DE 3825668 A 19880728; DE 58901679 T 19890712; JP 19159589 A 19890726