

Title (en)

CYLINDRICAL TAP SELECTOR WITH A CONTACT BRIDGE GUIDED BY A CANTILEVER MADE OF INSULATING MATERIAL

Publication

EP 0354425 B1 19930127 (DE)

Application

EP 89113948 A 19890728

Priority

DE 3827385 A 19880812

Abstract (en)

[origin: JPH02101721A] PURPOSE: To enable a support arm for a contact bridge to be surely fixed to a changing shaft, by a method wherein a projection engaged with a corresponding recess provided to a changing shaft is provided to a flange, and the flange is firmly linked to a changing shaft with a self-curing insulation band impregnated with resin. CONSTITUTION: A contact bridge 6 is supported and guided by a support arm 7 mounted on a changing shaft 3. All the arm 7 formed of insulating material is mounted on the changing shaft 3 together with a flange 8 suitable for the tubular changing shaft 3, nearly occupying one-third (nearly angle of 120 deg.) of the circumference of the changing shaft 3. Furthermore, a projection 9 is provided to the flange 8 of the support arm 7 and engaged with a corresponding recess provided to the changing shaft 3. Moreover, the support arm 7 is fixed to the changing shaft 3 with a self-curing insulating band 10 impregnated with resin. Therefore, the insulating material band 10 is wound around the flange projection 11 of the support arm 7 and the changing shaft 3.

IPC 1-7

H01F 29/02

IPC 8 full level

H01F 29/04 (2006.01); **H01F 29/02** (2006.01); **H01H 9/00** (2006.01)

CPC (source: EP KR US)

H01F 29/04 (2013.01 - KR); **H01H 9/0016** (2013.01 - EP US)

Cited by

EP0680062A3; EP0424631A1; WO2012097959A1

Designated contracting state (EPC)

AT DE ES FR SE

DOCDB simple family (publication)

EP 0354425 A1 19900214; **EP 0354425 B1 19930127**; AT E85151 T1 19930215; CN 1015036 B 19911204; CN 1040455 A 19900314; DE 3827385 A1 19900215; DE 3827385 C2 19901220; DE 58903391 D1 19930311; ES 2037350 T3 19930616; HU 201171 B 19900928; HU T51411 A 19900428; JP H02101721 A 19900413; KR 900003924 A 19900327; US 4931599 A 19900605

DOCDB simple family (application)

EP 89113948 A 19890728; AT 89113948 T 19890728; CN 89106385 A 19890811; DE 3827385 A 19880812; DE 58903391 T 19890728; ES 89113948 T 19890728; HU 382989 A 19890727; JP 20708989 A 19890811; KR 890011041 A 19890802; US 38942389 A 19890803