

Title (en)
INK FLOW CONTROL SYSTEM AND METHOD FOR AN INK JET PRINTER

Publication
EP 0354706 A3 19900801 (EN)

Application
EP 89307791 A 19890801

Priority
US 23064488 A 19880810

Abstract (en)
[origin: EP0354706A2] A piezoelectric pump 22 or equivalent transducer is mounted on or within an ink jet printhead and is used to modulate the frequency or amplitude, or both, of oscillations of a liquid meniscus at a liquid ejection orifice 17 of a nozzle plate 16. The liquid meniscus at the orifice 17 has a natural resonant frequency and amplitude with respect to its equilibrium position 19, and the above modulation is performed in a controlled timed relation with respect to the phase of the natural oscillations of the meniscus at the liquid ejection orifice 17.

IPC 1-7
B41J 2/045; **B41J 2/175**

IPC 8 full level
B41J 2/05 (2006.01); **B41J 2/02** (2006.01); **B41J 2/055** (2006.01); **B41J 2/14** (2006.01)

CPC (source: EP)
B41J 2/055 (2013.01); **B41J 2/1404** (2013.01); **B41J 2/14201** (2013.01); **B41J 2002/14387** (2013.01)

Citation (search report)

- [X] US 4296421 A 19811020 - HARA TOSHITAMI, et al
- [X] US 4580149 A 19860401 - DOMOTO GERALD A [US], et al
- [X] US 4672398 A 19870609 - KUWABARA TADASHI [JP], et al
- [X] US 4646110 A 19870224 - IKEDA MASAMI [JP], et al

Cited by
EP0678391A1; EP0738602A3; EP1510342A1; EP1302319A3; EP0621135A1; US5587727A; US6149259A; EP1172212A3; EP0805027A3; US5828391A; EP0510934A3; US5280310A; US5481281A; US7364277B2; US6761433B2; US7270403B2; WO2005102707A1; US6217159B1; US6382754B1

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
EP 0354706 A2 19900214; **EP 0354706 A3 19900801**; CA 1319561 C 19930629; JP H0288246 A 19900328

DOCDB simple family (application)
EP 89307791 A 19890801; CA 595739 A 19890405; JP 20778389 A 19890810