

Title (en)

THREAD-SPLICING APPARATUS AND METHOD FOR PREPARING THE THREAD ENDS

Publication

EP 0356767 B1 19920325 (DE)

Application

EP 89114610 A 19890808

Priority

DE 3828319 A 19880820

Abstract (en)

[origin: EP0356767A1] A thread splicing apparatus (20) serves for the knot-free connection of threads (10). In the apparatus are arranged a thread splicing chamber (22) and, at a distance from the thread splicing chamber (22), a tube (1) through which fluid flows. The tube (1) serves to receive a thread end (11) to prepare the latter for the splicing operation. The tube (1) possesses a rough inner surface (2, 3, 6) which makes knocking contact with the thread end (11). <??>In the method for preparing the thread ends, a fluid flows turbulently through the tube (1). The thread end (11) is knocked by the turbulent flow against the structured inner surface (2, 3, 6) of the tube (1) until the thread end (11) is free of rotation. <IMAGE>

IPC 1-7

B65H 69/06

IPC 8 full level

B65H 69/06 (2006.01); **D01H 15/00** (2006.01)

CPC (source: EP US)

B65H 69/063 (2013.01 - EP US); **B65H 2701/31** (2013.01 - EP US)

Designated contracting state (EPC)

CH DE FR GB IT LI

DOCDB simple family (publication)

EP 0356767 A1 19900307; **EP 0356767 B1 19920325**; DE 3828319 A1 19900222; DE 3828319 C2 19920305; DE 58901026 D1 19920430; JP H02163273 A 19900622; US 5175983 A 19930105

DOCDB simple family (application)

EP 89114610 A 19890808; DE 3828319 A 19880820; DE 58901026 T 19890808; JP 21311889 A 19890821; US 80895791 A 19911213