

Title (en)
CIRCUIT BREAKER WITH ARC GUN

Publication
EP 0359467 A3 19910612 (EN)

Application
EP 89309023 A 19890906

Priority
US 24298288 A 19880912

Abstract (en)
[origin: EP0359467A2] A circuit breaker having an arc impeller characterized by a circuit breaker mechanism having stationary and movable contacts operable between open and closed positions. A U-shaped member has a U-leg on opposite sides of the stationary contact and the U-shaped member is comprised of a ferromagnetic material for providing a magnetic field in a zone perpendicular to the path of current through the closed contacts so as to drive any arc away from the contacts into an adjacent arc extinguisher. A fiber barrier is located adjacent the stationary contacts, which emits a cooling gas during contact separation.

IPC 1-7
H01H 9/46

IPC 8 full level
H01H 9/30 (2006.01); **H01H 9/46** (2006.01); **H01H 33/04** (2006.01); **H01H 73/18** (2006.01)

CPC (source: EP KR)
H01H 9/46 (2013.01 - EP); **H01H 33/08** (2013.01 - KR)

Citation (search report)

- [Y] DE 1009698 B 19570606 - SIEMENS AG
- [Y] FR 78958 E 19621005
- [A] DE 2159756 B1 19730524
- [A] FR 2365874 A1 19780421 - SIEMENS AG [DE]
- [A] EP 0033479 A1 19810812 - CGE COMP GEN ELETTROMECC [IT]
- [AD] US 4654491 A 19870331 - MAIER ALFRED E [US], et al

Cited by
CN102592908A; FR2761194A1; EP2605265A4; JP2017515279A; US10026578B2; WO2015117998A2; US10068732B2; US10431406B2

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
EP 0359467 A2 19900321; **EP 0359467 A3 19910612**; AU 4012289 A 19900315; BR 8904551 A 19900424; CN 1041476 A 19900418; JP H02119018 A 19900507; KR 900005515 A 19900414; ZA 896375 B 19900530

DOCDB simple family (application)
EP 89309023 A 19890906; AU 4012289 A 19890822; BR 8904551 A 19890911; CN 89107060 A 19890911; JP 23550789 A 19890911; KR 890013220 A 19890912; ZA 896375 A 19890821