

Title (en)  
PRESSER FOOT FOR SEWING AND CUTTING

Publication  
**EP 0359713 B1 19930203 (DE)**

Application  
**EP 89810672 A 19890911**

Priority  
CH 341188 A 19880913

Abstract (en)  
[origin: EP0359713A1] The presser foot exchangeably attachable to a sewing machine comprises a cutting leg (47) connected fixedly to the presser foot (10) and a cutting leg (40) pivotable about an axle (45), the cutting movement being derived from the up-and-down movement of the needle bar (51). The purpose is served by a pivoting lever (20) which has essentially the form of an upturned letter T. The lever (20) is pivotable about an axle (21) connected to the foot (10), and its upwardly projecting arm bears with spring pressure against the needle- fastening screw (50). The arm flank bearing against the screw (50) forms an acute angle with the path of movement of the needle bar (51). When the sewing machine is in operation, therefore, the up-and-down movement of the needle bar (51) is converted into a pivoting movement of the lever (20). The pivoting movement of the lever (20) is transmitted, by a pin (41) fastened to it and engaging into a slot (42) of the pivotable cutting leg (40), to the latter. <??>This ensures in a simple and elegant way a reduction of the large needle-bar stroke into a much smaller stroke of the presser foot. <IMAGE>

IPC 1-7  
**D05B 37/06**

IPC 8 full level  
**D05B 29/08** (2006.01); **D05B 37/06** (2006.01)

CPC (source: EP US)  
**D05B 37/06** (2013.01 - EP US)

Designated contracting state (EPC)  
DE FR GB IT SE

DOCDB simple family (publication)  
**EP 0359713 A1 19900321**; **EP 0359713 B1 19930203**; CH 679409 A5 19920214; DE 58903442 D1 19930318; JP H02114989 A 19900427; US 5000104 A 19910319

DOCDB simple family (application)  
**EP 89810672 A 19890911**; CH 341188 A 19880913; DE 58903442 T 19890911; JP 23833589 A 19890913; US 40605189 A 19890912