

Title (en)  
ROLLER WITH A CORRUGATED SURFACE

Publication  
**EP 0360142 B1 19930804 (DE)**

Application  
**EP 89116934 A 19890913**

Priority  
CH 354088 A 19880923

Abstract (en)  
[origin: EP0360142A1] The invention relates to a device for increasing the adhesion length of slivers, in particular textile slivers. In the spinning process, efforts are made to give the fibres in the sliver a parallel alignment as far as possible. By this means, the adhesion length of the sliver is naturally reduced and leads to undesired sliver ruptures during the processing operation. <??>It is therefore proposed to pass the sliver (1) between two calender rollers (4, 5), the calender rollers being provided on their outer circumference with tooth-like elevations (16), the elevations (16) being able to engage in one another in the manner of a toothed wheel and being of small size. <IMAGE>

IPC 1-7  
**B65H 54/80; D01H 5/22**

IPC 8 full level  
**D01G 99/00** (2010.01); **B65H 54/80** (2006.01); **D01H 5/78** (2006.01)

CPC (source: EP US)  
**B65H 54/80** (2013.01 - EP US); **D01H 5/78** (2013.01 - EP US); **B65H 2701/31** (2013.01 - EP US)

Cited by  
WO2010012111A1; CN104328540A; EP4296414A1; WO2012071675A1

Designated contracting state (EPC)  
CH DE ES FR IT LI

DOCDB simple family (publication)  
**EP 0360142 A1 19900328; EP 0360142 B1 19930804**; DD 284926 A5 19901128; DE 58905128 D1 19930909; JP 2865729 B2 19990308;  
JP H02112421 A 19900425; US 5065477 A 19911119

DOCDB simple family (application)  
**EP 89116934 A 19890913**; DD 33286889 A 19890921; DE 58905128 T 19890913; JP 24357889 A 19890921; US 41031289 A 19890920