

Title (en)

X-RAY IMAGE INTENSIFIER

Publication

EP 0361266 A3 19901114 (DE)

Application

EP 89117243 A 19890918

Priority

DE 8812346 U 19880929

Abstract (en)

[origin: EP0361266A2] An X-ray image intensifier (5a) possesses an electrode system for focusing onto the output fluorescent screen (7) of the X-ray intensifier (5a) the electrons generated during infringement of the X-ray radiation on the input fluorescent screen (4) of the X-ray image intensifier (5a). Said electrode system is to be simplified, the number of electrodes being reduced and the imaging characteristics being improved. <??>According to the invention, the object is achieved when one electrode of the electron optics composed of electrically resistant material is applied as a coating (15) on a one-piece electrode carrier (14a) forming the jacket of the vacuum vessel, and a voltage is applied to the coating (15), so that the potential field rises continuously in the region from the input fluorescent screen (4) to the output fluorescent screen (7). <IMAGE>

IPC 1-7

H01J 29/62; H01J 29/88; H01J 31/50

IPC 8 full level

H01J 29/62 (2006.01); **H01J 31/50** (2006.01)

CPC (source: EP US)

H01J 29/622 (2013.01 - EP US); **H01J 31/501** (2013.01 - EP US)

Citation (search report)

- [X] FR 2231103 A1 19741220 - SOUTH AFRICAN INVENTIONS [ZA]
- [X] GB 471817 A 19370910 - TELEFUNKEN GMBH
- [A] DE 1035282 B 19580731 - FRITZ SCHNEIDER DR
- [A] GB 839681 A 19600629 - RAULAND CORP

Cited by

DE4213906A1; EP0721653A4

Designated contracting state (EPC)

DE FR

DOCDB simple family (publication)

EP 0361266 A2 19900404; EP 0361266 A3 19901114; DE 8812346 U1 19900201; JP H0250947 U 19900410; US 4996414 A 19910226

DOCDB simple family (application)

EP 89117243 A 19890918; DE 8812346 U 19880929; JP 11082989 U 19890920; US 41374489 A 19890922