

Title (en)

Use of a nozzle having a convergent-divergent profile in an ejection device for a root-cutter.

Title (de)

Verwendung einer Düse mit convergent-divergenten Profil in einer Ausstossvorrichtung eines Wurzelschneiders.

Title (fr)

Utilisation d'une buse présentant un profil convergent-divergent dans un dispositif de déboufrage de coupe-racines.

Publication

**EP 0363282 B1 19940420 (FR)**

Application

**EP 89402749 A 19891005**

Priority

FR 8813020 A 19881005

Abstract (en)

[origin: EP0363282A1] The invention relates to an ejection device for a beet slicer employed in the sugar industry, employing the projection of a jet of compressible fluid under pressure. The device comprises a nozzle (2) for injecting fluid, arranged on the static part (3) of the apparatus and pointing in the direction of the trajectory followed by the knives. This nozzle fed with fluid at a predetermined pressure, temperature and flow rate is characterised in that its profile is determined so as to ensure the isentropic pressure release of the fluid to a pressure close to the surrounding downstream pressure. <IMAGE>

IPC 1-7

**C13C 1/06**

IPC 8 full level

**B26D 7/08** (2006.01); **C13B 5/06** (2011.01)

CPC (source: EP)

**B26D 7/088** (2013.01); **C13B 5/06** (2013.01)

Citation (examination)

Dubbel, Taschenbuch für Maschinenbau, 1974, p.322

Designated contracting state (EPC)

BE DE ES FR GB GR IT NL SE

DOCDB simple family (publication)

**EP 0363282 A1 19900411**; **EP 0363282 B1 19940420**; DE 68914767 D1 19940526; DE 68914767 T2 19940804; ES 2051380 T3 19940616; FR 2637295 A1 19900406; FR 2637295 B1 19901214

DOCDB simple family (application)

**EP 89402749 A 19891005**; DE 68914767 T 19891005; ES 89402749 T 19891005; FR 8813020 A 19881005