Title (en)

COVERING FOR MASKING AN OPENING

Publication

EP 0363454 B1 19920513 (DE)

Application

EP 89902944 A 19890306

Priority

CH 109488 A 19880323

Abstract (en)

[origin: WO8909322A1] A divided flexible covering (1, 2) serves to expose any desired region of a surface or opening while masking the other regions. Two gripping slats (3, 10) are located respectively at the beginning of a length of fabric (1 or 2) or at the beginning and end of at least one or two strips (4 or 8), each of which is guided endlessly over four rollers (5, 9) or sliding blocks (47). Each length of fabric (1 or 2) is provided with an end piece (7 or 12). The length of the lengths of fabric (1 or 2) is approximately half that of the strips (4 or 8). The end pieces (7, 12) are mutually offset and are provided with a slot (14a) or are attached to a rod (43) provided for the other length of fabric, so that when a covering part (1), for example, is pulled down over the centre of the cupboard, the covering part (2) is pulled simultaneoulsy because one end piece (7) entrains another end piece (12) upward in the direction of traction. The operations are identical in the opposite direction. The gripping slats (3 and 10) and the end pieces (7 and 12) for unattached strips (4 and 8) have slits which ensure frictionless sliding.

IPC 1-7

E06B 9/40

IPC 8 full level

E06B 9/40 (2006.01); E06B 9/02 (2006.01); E06B 9/11 (2006.01); E06B 9/42 (2006.01)

CPC (source: EP US)

E06B 9/115 (2013.01 - EP US)

Cited by

EP1524400A1

Designated contracting state (EPC)

AT BE CH DE FR IT LI LU SE

DOCDB simple family (publication)

WO 8909322 A1 19891005; EP 0363454 A1 19900418; EP 0363454 B1 19920513; JP 2807520 B2 19981008; JP H02504053 A 19901122; US 5052459 A 19911001

DOCDB simple family (application)

EP 8900226 W 19890306; EP 89902944 A 19890306; JP 50272889 A 19890306; US 45534189 A 19891220