

Title (en)  
MECHANICAL LOCKING DEVICE

Publication  
**EP 0363957 A3 19910327 (DE)**

Application  
**EP 89118981 A 19891012**

Priority  
SU 4493189 A 19881014

Abstract (en)  
[origin: EP0363957A2] The subject of the invention is a mechanical locking device consisting of a lock and a key. The lock includes a releasable bolt (2) with an insertion head (5). Formed on the side face of the insertion head (5) is at least one longitudinal rib (7), the cross-sectional profile of which corresponds to that of code recesses (8) in code fixers (6) which are arranged in the housing (1) so as to be displaceable transversely relative to the insertion head (5). Each code fixer (6) has at least one additional recess (9), the width of which corresponds to the cross-sectional profile of the longitudinal rib (7) and the depth of which is smaller than the height of the longitudinal rib (7). <IMAGE>

IPC 1-7  
**E05B 27/08; E05B 19/18**

IPC 8 full level  
**E05B 35/00** (2006.01); **E05B 19/18** (2006.01); **E05B 27/08** (2006.01); **E05B 35/04** (2006.01); **E05B 37/20** (2006.01); **E05B 67/00** (2006.01)

CPC (source: EP US)  
**E05B 19/18** (2013.01 - EP US); **E05B 27/086** (2013.01 - EP US); **Y10T 70/7531** (2015.04 - EP US); **Y10T 70/7757** (2015.04 - EP US);  
**Y10T 70/7881** (2015.04 - EP US)

Citation (search report)  
• [X] US 4164857 A 19790821 - GENAKIS JOSEPH M  
• [Y] US 2302414 A 19421117 - JOHN BUCHANAN-WOLLASTON HUGO  
• [Y] FR 867917 A 19411205  
• [Y] US 2959951 A 19601115 - MIRKIN JORGE J  
• [Y] US 3855826 A 19741224 - HORI H  
• [A] US 3486353 A 19691230 - PILVET AKSEL

Designated contracting state (EPC)  
AT DE FR GB IT

DOCDB simple family (publication)  
**EP 0363957 A2 19900418; EP 0363957 A3 19910327**; CA 2000624 A1 19900414; CN 1041986 A 19900509; CS 582889 A2 19910813;  
DK 505789 A 19900415; DK 505789 D0 19891012; FI 894863 A0 19891013; HU 202304 B 19910228; HU 895297 D0 19900128;  
HU T51720 A 19900528; JP H02176081 A 19900709; RU 2093653 C1 19971020; US 5024071 A 19910618

DOCDB simple family (application)  
**EP 89118981 A 19891012**; CA 2000624 A 19891013; CN 89107937 A 19891014; CS 582889 A 19891013; DK 505789 A 19891012;  
FI 894863 A 19891013; HU 529789 A 19891012; JP 26528989 A 19891013; SU 4493189 A 19881014; US 43053089 A 19891101