

Title (en)

Billet for the production of composite materials.

Title (de)

Vormaterial für die Erzeugung von Verbundwerkstoffen.

Title (fr)

Ebauche pour la production des matériaux composites.

Publication

EP 0364430 A1 19900418 (DE)

Application

EP 89890232 A 19890905

Priority

AT 247988 A 19881007

Abstract (en)

The invention relates to a billet for the production of composite materials, consisting of a tubular outer part and at least one core or inner part and two sealing parts arranged on the end faces of the tubular outer part, and to a process for the production of the billet. For this purpose, provision is made for the sealing parts to project at least partially into the outer part, a surface pressure prevailing on the fitting surfaces, and, in comparison with the material of the outer part, the sealing parts being formed from a material with at least the same coefficient of expansion and with substantially the same deformation resistance, and with a higher softening temperature. The process according to the invention provides for a shrinking of the sealing parts into the tubular outer part with, if appropriate, subsequent evacuation or filling of the residual cavities with inert gas. <IMAGE>

Abstract (de)

Die Erfindung betrifft ein Vormaterial für die Herstellung von Verbundwerkstoffteilen bestehend aus einem rohrförmigen Außenteil und mindestens einem Kern oder Innenteil und zwei am rohrförmigen Außenteil stirnseitig angeordneten Verschluss teilen sowie einem Verfahren zur Herstellung des Vormaterials. Hierzu ist vorgesehen, daß die Verschluss teilen zumindest teilweise in den Außenteil ragen, wobei an den Paßflächen eine Flächenpressung herrscht und im Vergleich mit dem Werkstoff des Außenteiles die Verschluss teilen aus einem Werkstoff mit mindestens gleichem Ausdehnungskoeffizienten und mit im wesentlichen gleichen Formänderungswiderstand sowie einer höheren Erweichungtemperatur gebildet wird. Das erfindungsgemäße Verfahren sieht ein Einschrumpfen der Verschluss teilen in den rohrförmigen Außenteil mit einer gegebenenfalls nachfolgenden Evakuierung oder Füllung mit Inertgas der Resthohlräume vor.

IPC 1-7

B22F 3/12; B22F 7/08

IPC 8 full level

B22F 3/14 (2006.01); **B22F 3/04** (2006.01); **B22F 3/15** (2006.01); **B22F 7/06** (2006.01); **B22F 7/08** (2006.01)

CPC (source: EP US)

B22F 7/062 (2013.01 - EP US); **B22F 7/08** (2013.01 - EP US); **Y10T 29/49826** (2015.01 - EP US); **Y10T 29/49879** (2015.01 - EP US); **Y10T 428/12493** (2015.01 - EP US)

Citation (search report)

- [A] US 4016008 A 19770405 - FORBES JONES ROBIN MACKAY, et al
- [AD] US 4640815 A 19870203 - BROSIUS KARL S [US], et al
- [A] US 3941570 A 19760302 - COUCHMAN RICHARD
- [A] US 2348696 A 19440509 - ERIC SCHABACKER HENRY
- [A] US 4015765 A 19770405 - AHMED NAZEER

Cited by

WO9532819A1

Designated contracting state (EPC)

BE CH DE ES FR GB GR IT LI LU NL SE

DOCDB simple family (publication)

EP 0364430 A1 19900418; AT 391105 B 19900827; AT A247988 A 19900215; CN 1042323 A 19900523; FI 87743 B 19921113; FI 87743 C 19930225; FI 894694 A0 19891004; FI 894694 A 19900408; JP H02122003 A 19900509; NO 893933 D0 19891003; NO 893933 L 19900409; RU 2004383 C1 19931215; US 5004653 A 19910402

DOCDB simple family (application)

EP 89890232 A 19890905; AT 247988 A 19881007; CN 89107697 A 19891007; FI 894694 A 19891004; JP 25247989 A 19890929; NO 893933 A 19891003; SU 4742126 A 19891006; US 41667689 A 19891005