

Title (en)

MOTOR BOGIE FOR A RAILWAY VEHICLE WITH A LOW FLOOR OVER ITS WHOLE LENGTH

Publication

**EP 0364847 B1 19920617 (FR)**

Application

**EP 89118703 A 19891009**

Priority

FR 8813704 A 19881018

Abstract (en)

[origin: EP0364847A1] End motor bogie, or intermediate motor bogie between two bodies, for a railway vehicle having a low floor over its entire length, comprising: a) a load-bearing transom (31) carried via secondary suspensions (32, 33) by a frame (34) itself bearing via primary suspensions (35, 36, 35A, 36A) on two axles (39, 40) carrying the running wheels (41, 42, 43, 44), b) at least one motor connected to the axles by couplings and reduction gears, each motor driving the two wheels of a same axle in rotation, c) brake discs. It comprises two motors (45, 46), couplings (47, 48), reduction gears (51, 52) and brake discs (53) arranged laterally on either side and outside the running wheels. <IMAGE>

IPC 1-7

**B61C 9/52**; **B61D 13/00**; **B61F 3/04**; **B61F 5/52**

IPC 8 full level

**B61C 9/52** (2006.01); **B61D 13/00** (2006.01); **B61F 3/04** (2006.01); **B61F 5/52** (2006.01)

CPC (source: EP)

**B61C 9/52** (2013.01); **B61D 13/00** (2013.01); **B61F 3/04** (2013.01); **B61F 5/52** (2013.01)

Cited by

EP0829413A3; WO9629224A1; JP2017171288A

Designated contracting state (EPC)

AT BE CH DE ES FR GB IT LI NL SE

DOCDB simple family (publication)

**EP 0364847 A1 19900425**; **EP 0364847 B1 19920617**; AT E77317 T1 19920715; CA 2000750 A1 19900418; CA 2000750 C 19990525; DE 68901847 D1 19920723; DE 68901847 T2 19921217; ES 2033064 T3 19930301; FR 2637861 A1 19900420; FR 2637861 B1 19910426; PT 92012 A 19900430; PT 92012 B 19950809

DOCDB simple family (application)

**EP 89118703 A 19891009**; AT 89118703 T 19891009; CA 2000750 A 19891016; DE 68901847 T 19891009; ES 89118703 T 19891009; FR 8813704 A 19881018; PT 9201289 A 19891017