

Title (en)

LOCKING DEVICE

Publication

EP 0364878 B1 19930616 (DE)

Application

EP 89118930 A 19891012

Priority

DE 3835913 A 19881021

Abstract (en)

[origin: EP0364878A2] The invention relates to a locking device on doors equipped with an inner and an outer fitting (2, 3) and a lock (5) arranged between the two fittings and actuatable from inside and outside and, to achieve a substantial benefit in terms of use to the effect that remote call-up of the locking state and/or storage of locking operations which have taken place is possible, proposes, whilst ensuring a simple constructional form, that there be at least one switch disc (19, 19a) taken up during the actuation of the lock and a contact or switch (S1, S2) assigned to the latter for generating electrical recording signals relating to the lock actuation, and/or that an inner and an outer call-up should take place. <IMAGE>

IPC 1-7

E05B 17/22

IPC 8 full level

E05B 49/00 (2006.01); **E05B 17/22** (2006.01); **E05B 47/00** (2006.01)

CPC (source: EP US)

E05B 17/22 (2013.01 - EP US); **E05B 47/0012** (2013.01 - EP US); **E05B 49/00** (2013.01 - EP US); **E05B 2047/002** (2013.01 - EP US);
Y10T 70/7062 (2015.04 - EP US)

Cited by

US2015137536A1; DE4315892A1; DE19654443A1; US11443572B2; US9103141B2; WO2011065887A1

Designated contracting state (EPC)

AT BE CH DE ES FR GB GR IT LI NL SE

DOCDB simple family (publication)

EP 0364878 A2 19900425; **EP 0364878 A3 19910102**; **EP 0364878 B1 19930616**; AT E90767 T1 19930715; DE 3835913 A1 19900503;
DE 58904714 D1 19930722; JP H02186080 A 19900720; JP H02186081 A 19900720; JP H07113294 B2 19951206;
JP H07119533 B2 19951220; US 5057830 A 19911015

DOCDB simple family (application)

EP 89118930 A 19891012; AT 89118930 T 19891012; DE 3835913 A 19881021; DE 58904714 T 19891012; JP 23677589 A 19890912;
JP 27477189 A 19891021; US 42314989 A 19891018