

Title (en)

TIPPING AND/OR LIFTING MECHANISM

Publication

EP 0365522 A4 19901010 (EN)

Application

EP 88900558 A 19871222

Priority

- AU PI164787 A 19870429
- AU PI521487 A 19871103

Abstract (en)

[origin: WO8808378A1] A tipping mechanism (20) has a pair of parallel side beams (24) mounted in the chassis of a trailer. An operating arm (21) is supported between guide plates (23, 23a) and is movable longitudinally by a hydraulic ram (27). The lifting arm (31) is hingedly mounted on side plates (32) and has a roller (33) at its distal end to engage a track on the underside of a load body hingedly mounted on the chassis. A link (35) interconnects the operating arm (21) and lifting arm (31) so that as the operating arm (21) is moved by the ram (27) the lifting arm (31) is raised or lowered in a two-stage action, the link (35) pivoting about a pin (36) on the operating arm (21). Modifications allow the mechanism to be used in a trolley jack and to achieve straight vertical lifting of a load body when vertical guides are employed.

IPC 1-7

B60P 1/16; B66F 5/04; B66F 7/08

IPC 8 full level

B60P 1/20 (2006.01); **B66F 5/04** (2006.01); **B66F 7/08** (2006.01); **B66F 7/22** (2006.01)

CPC (source: EP KR)

B60P 1/16 (2013.01 - KR); **B60P 1/20** (2013.01 - EP); **B66F 5/04** (2013.01 - EP); **B66F 7/0625** (2013.01 - EP); **B66F 7/0633** (2013.01 - EP);
B66F 7/0641 (2013.01 - EP); **B66F 7/08** (2013.01 - EP); **B66F 7/22** (2013.01 - EP)

Citation (search report)

- [X] FR 844662 A 19390731 - THEVENET ET CLERJOUNIE
- [Y] FR 1451996 A 19660909
- See references of WO 8808378A1

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

WO 8808378 A1 19881103; EP 0365522 A1 19900502; EP 0365522 A4 19901010; ES 2006922 A6 19890516; KR 890700492 A 19890425;
MY 103081 A 19930430; NZ 223077 A 19900327

DOCDB simple family (application)

AU 8700434 W 19871222; EP 88900558 A 19871222; ES 8801300 A 19880428; KR 880701780 A 19881229; MY PI19880456 A 19880429;
NZ 22307787 A 19871223