

Title (en)

NOVEL GEL PRODUCING PAD AND IMPROVED METHOD FOR SURFACING AND POLISHING LENSES

Publication

EP 0366051 B1 19930310 (EN)

Application

EP 89119666 A 19891024

Priority

US 26283888 A 19881026

Abstract (en)

[origin: EP0366051A1] A surfacing pad (10) is produced by dispersing abrasive particles (17) in a flexible, water absorbent matrix (16) that is secured on a flexible, fabric substrate (14), which functions as a reservoir for a liquid. By applying to the pad (10) a small quantity of liquid sufficient to wet the matrix (16) and to saturate the substrate (14), it is possible by rubbing the surfaces of a workpiece and the wetted matrix (16) to create an abrasive surfacing gel between the workpiece and the pad (10) substrate, thus eliminating the need for directing a slurry or other liquid onto the workpiece during a surfacing operation.

IPC 1-7

B24D 3/20

IPC 8 full level

B24B 13/01 (2006.01); **B24B 29/00** (2006.01); **B24D 3/00** (2006.01); **B24D 3/02** (2006.01); **B24D 3/20** (2006.01); **B24D 3/34** (2006.01); **B24D 9/08** (2006.01); **B24D 11/00** (2006.01)

CPC (source: EP)

B24B 13/01 (2013.01); **B24D 3/002** (2013.01); **B24D 3/20** (2013.01)

Cited by

KR100750759B1; US5368619A; US5470368A; US5496387A; USRE35709E; US7503834B2; US6638144B2; WO9413434A1; WO0183163A3; EP0438671B1; WO2022237200A1; EP1711311B2

Designated contracting state (EPC)

BE DE FR GB IT NL

DOCDB simple family (publication)

EP 0366051 A1 19900502; **EP 0366051 B1 19930310**; CA 2001487 A1 19900426; CA 2001487 C 19940322; DE 68905297 D1 19930415; DE 68905297 T2 19930617; JP 2796678 B2 19980910; JP H02167662 A 19900628; MX 171378 B 19931021

DOCDB simple family (application)

EP 89119666 A 19891024; CA 2001487 A 19891025; DE 68905297 T 19891024; JP 27697789 A 19891024; MX 1809389 A 19891025