

Title (en)

METHOD AND DEVICE FOR ADVANCING PRINTED ARTICLES

Publication

EP 0368009 B1 19930616 (DE)

Application

EP 89118844 A 19891011

Priority

CH 420288 A 19881111

Abstract (en)

[origin: EP0368009A1] The printed articles (12) are arranged on the advancing device (10) in an imbricated formation (S), in which two printed articles (12) lying one on top of the other rest in each case in an imbricated manner on a pair of subsequent printed articles (12). The printed articles (12) are advanced with their leading edges (32) towards a stop (16). The top one of the printed articles (12) waiting in each case at the stop (16) is lifted by means of the lifting element (40) in the region of the side edge (36') and gripped from below by the slide element (42). By displacing the slide element (42) in the direction towards the stop element (38), the printed article (12') is curved upwards. In the region of the curvature, this printed article (12') is gripped from below by a telescopically extensible transport belt (48') and transported away. <IMAGE>

IPC 1-7

B65H 29/66; **B65H 29/70**

IPC 8 full level

B65H 29/66 (2006.01); **B65H 29/70** (2006.01)

CPC (source: EP US)

B65H 29/6609 (2013.01 - EP US); **B65H 29/6654** (2013.01 - EP US); **B65H 29/669** (2013.01 - EP US); **B65H 29/70** (2013.01 - EP US); **B65H 2301/44472** (2013.01 - EP US); **B65H 2301/44712** (2013.01 - EP US); **B65H 2301/44732** (2013.01 - EP US)

Cited by

EP0551601A1; EP1364900A1; DE19627830B4; EP2017209A1; US7784784B2

Designated contracting state (EPC)

AT CH DE FR GB IT LI SE

DOCDB simple family (publication)

EP 0368009 A1 19900516; **EP 0368009 B1 19930616**; AT E90648 T1 19930715; CA 2002720 A1 19900511; DE 58904720 D1 19930722; JP 2736137 B2 19980402; JP H02178161 A 19900711; US 5042792 A 19910827

DOCDB simple family (application)

EP 89118844 A 19891011; AT 89118844 T 19891011; CA 2002720 A 19891110; DE 58904720 T 19891011; JP 28806389 A 19891107; US 43633089 A 19891113