

Title (en)

GLUEING SEGMENT TO BE SLIPPED AND CLAMPED ONTO A DRIVE SHAFT

Publication

EP 0368010 B1 19920304 (DE)

Application

EP 89118862 A 19891011

Priority

DE 3837362 A 19881103

Abstract (en)

[origin: EP0368010A1] The invention relates to a glueing segment 1,2 which can be slipped onto a drive shaft 3 and clamped by means of a pulling bolt 18, 19. The pulling bolt 18, 19 penetrates a continuously slotted wall between an axial bore hole 10, 11, which is arranged in the central point of curvature of the glue-receiving surface 4, 5, and a plugging receptacle 12, 13 for the drive shaft 3 arranged between said axial bore hole 10, 11 and the glue-receiving surface 4, 5. The bolt 18, 19 penetrates the axial bore hole 10, 11 and a bush 21, 22 which is inserted in the axial bore hole 10, 11 and bears as a spacer element a collar 27, 28 supported on the outer edge 29 of the axial bore hole 10, 11 or another abutment 30 and serving as a spacer element. The collar 27, 28 originally has a large height so that it can be shortened to the required spacer height. The spacer element is held captively on the glueing segment 1,2 by the pulling bolt 18, 19 penetrating it. <IMAGE>

IPC 1-7

B65C 9/16

IPC 8 full level

B65C 9/16 (2006.01)

CPC (source: EP US)

B65C 9/16 (2013.01 - EP US); **Y10T 156/1773** (2015.01 - EP US); **Y10T 156/178** (2015.01 - EP US); **Y10T 156/1798** (2015.01 - EP US)

Designated contracting state (EPC)

DE ES FR GB IT

DOCDB simple family (publication)

EP 0368010 A1 19900516; **EP 0368010 B1 19920304**; CA 2002232 A1 19900503; DE 3837362 C1 19900621; DE 58900924 D1 19920409; ES 2030572 T3 19921101; US 5062918 A 19911105

DOCDB simple family (application)

EP 89118862 A 19891011; CA 2002232 A 19891103; DE 3837362 A 19881103; DE 58900924 T 19891011; ES 89118862 T 19891011; US 43211389 A 19891103