

Title (en)  
PROCESS FOR DRYING COATED WEB

Publication  
**EP 0368289 A3 19911218 (EN)**

Application  
**EP 89120720 A 19891108**

Priority  
JP 28140888 A 19881109

Abstract (en)  
[origin: EP0368289A2] A process for drying a coated web which comprises drying a continuously traveling web coated with a coating composition containing an organic solvent by hot air up to set to touch, and evaporating the residual solvent in the coated membrane by heating a heating roll. In the process of the invention, since a coated web is first dried by a hot air at a relatively low temperature, such as lower than 150 DEG C, up to set to touch state and then further dried by a heating roll being excellent in heat conductivity, a temperature distribution occurs little in the cross direction. Moreover, the present drying process rarely affects adversely the coated membrane of the web.

IPC 1-7  
**G03C 1/74**; **F26B 3/00**

IPC 8 full level  
**B05D 3/02** (2006.01); **F26B 3/00** (2006.01); **F26B 13/10** (2006.01); **G03C 1/74** (2006.01); **G03F 7/16** (2006.01)

CPC (source: EP US)  
**F26B 3/00** (2013.01 - EP US); **F26B 13/10** (2013.01 - EP US); **G03C 1/74** (2013.01 - EP US); **G03F 7/168** (2013.01 - EP US);  
**G03C 2001/7451** (2013.01 - EP US)

Citation (search report)  
• [Y] US 3674534 A 19720704 - CONNAIR MICHAEL JOHN  
• [X] PATENT ABSTRACTS OF JAPAN, vol. 11, no. 285 (P-616)(2732) 16 September 1987; & JP-A-62 081 637 (MITSUBISHI PAPER MILLS LTD.) 15 April 1987  
• [Y] RESEARCH DISCLOSURE, vol. 203, no. 34, March 1981, HAVANT, GB; page 130; 'Method for drying magnetic recording regions on photographic elements'.

Cited by  
EP1172697A3; EP1172697A2; WO2009068551A1

Designated contracting state (EPC)  
DE NL

DOCDB simple family (publication)  
**EP 0368289 A2 19900516**; **EP 0368289 A3 19911218**; **EP 0368289 B1 19950913**; DE 68924240 D1 19951019; DE 68924240 T2 19960215; JP H02131174 A 19900518; JP H0649175 B2 19940629; US 5077912 A 19920107

DOCDB simple family (application)  
**EP 89120720 A 19891108**; DE 68924240 T 19891108; JP 28140888 A 19881109; US 43327089 A 19891108