

Title (en)
LOCATOR FOR A CRIMPING TOOL

Publication
EP 0368825 B1 19930908 (DE)

Application
EP 89850367 A 19891025

Priority
SE 8804084 A 19881111

Abstract (en)
[origin: EP0368825A2] For each punch element pair (21A/22A etc.) the locator (40) has one gripping element (41A etc.) for receiving an electrical connection element (30). The gripping element(s) is(are) borne by a support member (41, 42) which can be displaced in a straight line between a standby position in which the gripping element(s) (41A etc.) is(are) located in the region between the opened jaws (21, 22) of the crimping tool (10) and a starting position in which they are located completely outside this region. <IMAGE>

IPC 1-7
H01R 43/04

IPC 8 full level
H01R 43/04 (2006.01)

CPC (source: EP US)
H01R 43/04 (2013.01 - EP US)

Cited by
DE102007005176A1; DE10134004C1; DE102008017366A1; DE19641218A1; DE19641218C2; DE102007005176B4; US8161789B2; US9413129B2

Designated contracting state (EPC)
DE ES FR GB IT SE

DOCDB simple family (publication)
EP 0368825 A2 19900516; EP 0368825 A3 19901205; EP 0368825 B1 19930908; DE 58905527 D1 19931014; ES 2045557 T3 19940116; SE 8804084 D0 19881111; US 4982594 A 19910108

DOCDB simple family (application)
EP 89850367 A 19891025; DE 58905527 T 19891025; ES 89850367 T 19891025; SE 8804084 A 19881111; US 43530089 A 19891109